

Contents

1	Introduction	1
1.1	Introduction	1
1.2	Motivation	1
1.3	Problem Definition	1
1.4	Problem Solution Approach	2
2	Background and Related Work	3
2.1	Dynamic Spectrum Access(DSA)	3
2.2	Cognitive Radio Network(CRN)	4
2.3	Common Control channels(CCC)	4
2.4	Routing in CRN	5
2.4.1	Spectrum Aware Mesh Routing in Cognitive Radio Networks(SAMER)	5
2.4.2	Spectrum Aware On Demand Routing Protocol(SORP)	6
2.4.3	Local Coordination Based Routing and Spectrum Assignment	6
2.4.4	Virtual Backbone in CRN Without using Common Control Channel	6
3	Proposed Routing Solution	8
3.1	Network Model	8
3.2	Virtual Backbone Generation	9
3.2.1	Local Zone State and Connectivity Maintenance	9
3.2.2	The Distributed Database Coverage Heuristic for Virtual Backbone Generation	10
3.2.3	Normal State Node and Database Node Connectivity Maintenance	13
3.2.4	Dynamic Virtual Backbone Structural Maintenance	18
3.2.5	Redundancy Elimination in Virtual Backbone	18
3.3	Backbone Nodes Inter-Connectivity	19
3.3.1	Dynamic Virtual Backbone Connectivity Maintenance	19
3.4	Routing Using Virtual Backbone	27
3.4.1	A Modified Strategy For Routing Using Backbone Structure	29
3.4.2	Route Repair	35
4	Simulation Setup and Performance Evaluation	38
4.1	Simulation Platform : OMNeT++	38
4.2	Simulation Environment	39
4.3	Performance Metrics	41
4.3.1	Packet Delivery Ratio :	41
4.3.2	Throughput	41
4.3.3	Packet Loss	42
4.3.4	End-to-End Delay	42
4.4	Simulation Results and Discussion	42
4.4.1	Scenario 1 : Throughput for evaluating channel adaptivity	42
4.4.2	Scenario 1 : End-To-End Delay for evaluating channel adaptivity	43
4.4.3	Scenario 2 : Throughput for performance evaluation	44
4.4.4	Scenario 2 : Packet Delivery Ratio for performance evaluation	45
4.4.5	Scenario 2 : Packet Loss for performance evaluation	45
5	Conclusion and Future Work	47

List of Figures

2.1	Spectrum Utilization [1]	3
2.2	CRN Architecture [1]	4
2.3	Example of SAMER [6]	5
2.4	Example of SORP [14]	6
2.5	Example of Local Coordination based Routing [14]	7
2.6	Example of the end-to-end transmission using virtual backbone.	7
3.1	Routing zone formed by nodes with $r=4mW$	9
3.2	Connect Packet Format	10
3.3	Data Structure representing Link state table	10
3.4	Layout showing connect packet exchange	10
3.5	State Packet Format	11
3.6	Layout showing state packet exchange by <i>host[2]</i>	12
3.7	Layout showing state packet exchange by <i>host[3]</i>	13
3.8	Database Connect Packet Format	13
3.9	Layout showing database connect packet sent by <i>host[7]</i>	14
3.10	Database ACK Packet Format	14
3.11	Flow Chart for virtual backbone generation	16
3.12	Layout showing sending of database ACK	18
3.13	Layout showing several other database nodes in zone of a database node	19
3.14	Database Notification Packet Format	20
3.15	Database Notification ACK Packet Format	20
3.16	Layout showing sending of database notification packet by <i>host[1]</i>	21
3.17	Layout showing sending of notification ACK packet	22
3.18	Example showing Gateway Node	22
3.19	Gateway Notification Packet Format	22
3.20	Gateway Notification ACK Format	23
3.21	Flow Chart for interconnecting database nodes	25
3.22	Route Request Packet Format	27
3.23	Layout showing sending of RREQ by <i>host[0]</i>	28
3.24	Layout showing forwarding of RREQ by <i>host[1]</i> on receiving from <i>host[0]</i>	28
3.25	Route Reply Packet Format	29
3.26	Layout showing sending of RREP by <i>host[7]</i>	30
3.27	Flow Chart for route query during routing using virtual backbone	31
3.28	Flow Chart for route feedback during routing using virtual backbone	34
3.29	Flow Chart for route designation during routing using virtual backbone	36
4.1	An OMNeT++ model	38
4.2	Topological representation of proposed network	40
4.3	Throughput of AODV and VBR with respect to Network Load	43
4.4	End-to-End Delay of AODV and VBR with respect to Network Load	44
4.5	Throughput of AODV and VBR with respect to Number of Connections	44
4.6	PDR of AODV and VBR with respect to Number of Connections	45
4.7	Packet Loss of AODV and VBR with respect to Number of Connections	45

List of Tables

4.1	Table showing number of radios assigned to each CR node	40
4.2	Table showing channel number tuned to each radio	40
4.3	Simulation setup and parameter settings	41
4.4	Scenario 1: Variation in network load for evaluating channel adaptivity	42
4.5	Scenario 2: Variation in number of connections for performance evaluation	42