

Contents

1. Introduction	1
1.1 Sensor Networks.....	1
1.2 Evolution of LR-WPAN Standardization.....	1
1.3 ZigBee and IEEE 802.15.4.....	2
1.4 ZigBee vs. Bluetooth.....	2
1.5 Sensor Networks Applications.....	3
1.6 IEEE 802.15.4e.....	3
1.7 Work Done.....	4
1.8 Organization of the Report.....	4
2. Anatomy of a Sensor Network	5
2.1 The Architecture.....	5
2.2 Sensor Network Characteristics.....	5
2.3 Energy Efficiency.....	6
2.4 Performance Metrics.....	8
2.5 Localization.....	8
2.6 Communication Models.....	9
2.7 Routing.....	10
2.8 Data Delivery Models.....	11
2.9 Media Access Control in Sensor Networks.....	12
2.10 Network Dynamics Models.....	12
2.11 Sensor Networking Systems.....	14

3. IEEE 802.15.4 LR-WPAN	16
3.1 Components of WPAN.....	16
3.2 Network Topologies.....	16
3.2.1 Star Topology.....	16
3.2.2 Peer-to-Peer Topology.....	16
3.2.3 Cluster-Tree Topology.....	17
3.3 LR-WPAN Device Architecture.....	17
3.4 IEEE 802.15.4 PHY.....	18
3.4.1 Receiver Energy Detection (ED).....	19
3.4.2 Link Quality Indication (LQI).....	20
3.4.3 Clear Channel Assessment (CCA).....	20
3.4.4 PPDU Format.....	20
3.5 IEEE 802.15.4 MAC.....	21
3.5.1 Superframe Structure.....	21
3.5.2 CSMA-CA Algorithm.....	22
3.5.3 Data Transfer Model.....	25
3.5.4 Starting and Maintaining PANs.....	28
3.5.5 Beacon Generation.....	29
3.5.6 Association and Disassociation.....	30
3.5.7 Synchronization.....	33
3.5.8 Transmission, Reception and Acknowledgement.....	34
3.5.9 GTS Allocation and Management.....	35
3.5.10 MAC Frame Formats.....	36

4. The IEEE 802.15.4e Standard	37
4.1 An Industrial Case Study.....	37
4.2 Analytical Protocol Evaluation of IEEE 802.15.4 MAC layer CSMA/CA algorithm.....	37
4.3 Limitation Analysis.....	39
4.4 Removal of Limitations.....	39
4.5 IEEE 802.15.4e and its Performance Analysis.....	40
4.5.1 Analytical Protocol Evaluation of IEEE 802.15.4e MAC layer CSMA/CA algorithm.....	42
5. Proposed Modifications in IEEE 802.15.4e and Slot Allocation Rules for Cluster Tree Topology	44
5.1 Modification1: Allocation of last GTS slot to a device with higher priority in the beacon tracking enabled mode.....	44
5.2 Modification 2: Accommodation of more devices in the superframe structure with even lesser guaranteed latency.....	44
5.3 Rules for Slot Allocation for IEEE 802.15.4e for a hierarchical WSN setup.....	45
6. Simulation based Experimental Results	48
7. Conclusion and Future Work	57
References	59