

Contents

Contents	vii
List of Figures	ix
1 Introduction	1
1.1 Overview	1
1.2 Constrains in Cognitive Radio Networks	2
1.2.1 Heterogeneity	2
1.2.2 Multi channel Hidden Terminal Problem	2
1.2.3 Research Contributions	4
1.2.4 Organization of dissertation	4
2 Background and related works	5
2.1 Background	5
2.1.1 MAC protocol for Wireless Networks	5
2.1.2 Cognitive Radio based Networks	6
2.1.3 MAC Protocol for Cognitive Radio Networks	8
2.2 Literature Review	8
2.3 Cooperative MAC protocols for Homogenous CRNs	10
2.4 Comparison of different MAC protocols for DCRNs	11
2.5 Problem Statement	11
3 Non-cooperative MAC protocol for Heterogeneous Cognitive Radio Networks (NC-MAC)	12
3.1 SYSTEM MODEL	12
3.2 Control Frames in proposed MAC protocol	13
3.2.1 Frame Control	13

3.2.2	Duration	14
3.2.3	Receiver Address(RA)	14
3.2.4	Transmitter Address(TA)	14
3.2.5	Available DATA Channels	14
3.2.6	DATA Length	14
3.2.7	Frame Check Sequence(FCS)	14
3.3	Detailed Explanation of proposed Model	15
3.3.1	Spectrum Sensing Phase	16
3.3.2	Negotiation Phase	17
3.3.3	DATA transmission Phase	18
4	Performance evaluation and result analysis	20
4.1	Analysis of the proposed MAC protocol	20
4.2	Performance Evaluation and Results	24
5	Conclusion and Future Work	26
5.1	Conclusion	26
5.2	Future work	26
	Bibliography	28

List of Figures

1.1	The use of Spectrum	1
1.2	A typical scenario of heterogeneous radio resource availability in distributed CR network at a particular time instant. (Chx: represents a channel X which can be a combination of frequency band (or code) and/or time slot based on PU system implementation).	3
1.3	A scenario showing the multi-channel hidden terminal problem (SU C is a hidden terminal to SU B	3
2.1	Spectrum holes	6
2.2	Cognitive Cycle.	7
2.3	Classification of CR MAC protocols based on Infrastructure and Access Methods.	9
3.1	Control frame format	14
3.2	Principle of our proposed MAC protocol scheme.	15
3.3	ON-OFF Primary User usage model.	16
3.4	Flow chart of our proposed MAC protocol Scheme.	19
4.1	Saturation throughput vs PU utilization.	24
4.2	Saturation throughput vs number of SUs where the PU utilization is 0.3.	25
4.3	Saturation Vs number of SUs where the PU utilization is 0.8.	25