

Table of Contents

Acknowledgement	iii
Abstract.....	iv
1. Introduction.....	1
1.1 Overview of the problem	1
1.2 Motivation.....	2
1.3 Problem Statement.....	2
1.4 Contribution	3
1.5 Organization of the thesis	3
2. Background and Related Work.....	4
2.1 Wireless LAN	4
2.2 IEEE 802.11 Architecture	4
2.3 The Basic Access Method: CSMA/CA.....	5
2.4 Virtual Carrier Sense.....	7
2.5 Inter Frame Spaces.....	8
2.6 Exponential Back-off Algorithm	8
2.7 IEEE 802.11 Distributed Co-ordinated Function	9
2.8 Related Work	11
2.9 Performance Metrics	13
2.9.1 Throughput.....	13
2.9.2 Delay	16
3. Proposed Mechanism.....	17
3.1 Necessary Network Architecture	17
3.2 Problem Definition.....	17
3.3 Proposed Idea	18
4. Performance Study.....	19
4.1 Simulation Environment	19
4.2 Results and Analysis	20
4.3 Summary of Performance Study	26

5. Conclusion and Future work.....	27
5.1 Conclusion	27
5.2 Future work	27
References	28

List of Figures

Fig. 1.1: DIFS overhead	2
Fig. 2.1: Different modes in 802.11 network (adopted from Reference [3.1])	4
Fig. 2.2: Components of 802.11 LAN(adopted from Reference [3.2]).....	5
Fig. 2.3: CSMA/CA protocol (adopted from Reference [3.3])	6
Fig. 2.4: NAV setting of neighbours (adopted from Reference [3.4])	7
Fig. 2.5: Access mechanism diagram	9
Fig. 2.6: Sequential increase in CW values.....	10
Fig. 2.7: Basic Access Mechanism.....	11
Fig. 3.1: Standard DCF protocol	18
Fig. 3.2: Modified DCF protocol.....	18
Fig. 4.1: Avg. throughput as a function of network load for 10 nodes	21
Fig. 4.2: Avg. delay as a function of network load for 10 nodes	22
Fig. 4.3: Avg. throughput as a function of network load for 20 nodes	23
Fig. 4.4: Avg. delay as a function of network load for 20 nodes	24
Fig. 4.5: Avg. throughput as a function of network load for 50 nodes	24
Fig. 4.6: Avg. delay as a function of network load for 50 nodes	25

List of Tables

Table 4.1: System Parameter Values.....	22
Table 4.2: Simulation Parameter Values.....	23