

Table of Contents

Chapter	Topics	Page No.
CHAPTER 1	Introduction	1
	1.1 Problem Definition	2
	1.2 Motivation behind the Proposed Scheme	2
	1.3 Goals of the Proposed Scheme	3
CHAPTER 2	Background and Related Work	4
	2.1 Background	4
	2.1.1. Primary VS Secondary Devices	4
	2.1.2. Spectrum holes / Spectrum Opportunities	4
	2.1.3. Dynamic Spectrum Access	4
	2.2 Related Work	4
	2.2.1. Full Spectrum Knowledge	5
	2.2.1.1. Graph Based Approach	5
	2.2.1.1.1. Routing through layered-graphs	6
	2.2.1.1.2. Routing through colored-graphs	7
	2.2.1.1.3. Routing and spectrum selection through conflict-graphs	7
	2.2.1.2. Mixed Integer Non-Linear Programming	8
	2.2.2. Local Spectrum Knowledge	8
	2.2.2.1. Interference and power based solutions	9
	2.2.2.1.1. Minimum power routing	9
	2.2.2.1.2. Bandwidth footprint minimization	10
	2.2.2.1.3. Controlled interference routing	11
	2.2.2.2. Delay Based Solution	11
	2.2.2.2.1. Solutions accounting for switching and access delay	11
	2.2.2.2.2. Solutions accounting for queuing delay	12
	2.2.2.2.3. Effective transmission time routing	13
	2.2.2.3. Throughput Based Solution	14
	2.2.2.3.1. Path spectrum availability routing	14
	2.2.2.3.2. Spectrum utility based routing	14
	2.2.2.4. Link quality/stability based solutions	15
	2.2.2.4.1. Solutions with enhanced path recovery functionalities	16
	2.2.2.4.2. Solutions targeting route stability	16
	2.2.2.4.3. Routing with mobile SUs	17
	2.2.2.5. Probabilistic approaches	17
CHAPTER 3	Proposed Protocol	19
	3.1 System Model	19
	3.1.1. Node Model	19

3.1.2. Channel Model	19
3.1.3. Network Model	19
3.2 Data Structures and Route Metric Computation	19
3.3 Overall Design	21
CHAPTER 4 Performance Evaluation	24
4.1 Simulation Model	24
4.2 Observations	31
CHAPTER 5 Conclusion and Future Directions	32
5.1 Summary	32
5.2 Future Directions	32
References	33