

Table of Contents

Acknowledgement	i-ii
Abstract	iii-v
Table of Content	vi-xiii
List of Tables	xiv-xvi
List of Figures	xvii-xxi
List of Abbreviations	xxii

Chapter 1: Introduction

1.1. Introduction	1-2
1.2. Importance of Biomass	2-4
1.3. Biomass resources	4-5
1.3.1. Forest residues	5-6
1.3.2. Urban wastes and other wastes	6-7
1.3.3. Energy crops (woody energy crops and perennial herbaceous crops)	7-8
1.3.4. Aquatic biomass	8-9
1.4. Biofuels	9-10
1.4.1. First-generation biofuels	10-11
1.4.2. Second-generation biofuels	11
1.4.3. Third-generation biofuels	11
1.5. Conversion technologies	12-14
1.6. History of pyrolysis	15
1.7. Pyrolysis process	15-16
1.7.1. Conventional Pyrolysis	16-17
1.7.2. Fast Pyrolysis	17
1.7.3. Other Technologies	17
1.7.3.1. Carbonization	17-18
1.7.3.2. Flash pyrolysis	18
1.7.3.3. Gasification	18-19
1.7.3.4. Hydrothermal liquefaction (HTL)	19-20

1.8.	Pyrolysis products	20
1.8.1.	Biooil	20-21
1.8.2.	Char	21
1.8.3.	Gases	21-22
1.9.	Mechanism of pyrolysis	22-24
1.10.	Response surface methodology (RSM) as a tool for optimization	24-25
1.11.	Pyrolysis kinetic studies	25-26
1.12.	Application of pyrolysis products	26
1.12.1.	Application of Biooil	26-27
1.12.2.	Application of solid char	27-28
1.13.	Justification for selection of feedstock	28-31
1.14.	Objectives of doctoral research	31
	References	32-39

Chapter-2: Literature Review

2.1.	Introduction	40-41
2.2.	Pyrolysis of lignocellulosic biomass	41-43
2.2.1.	Pyrolysis of seed covers	43-45
2.2.2.	Pyrolysis of microalgae biomass	45-46
2.3.	Effects of pyrolysis parameters on product yields	46
2.3.1.	Effect of Pyrolysis Temperature	46-47
2.3.2.	Effect of Heating Rate	47
2.3.3.	Biomass composition	47-48
2.4.	Pyrolysis mechanism	49
2.5.	Thermogravimetric analysis of biomass	49-51
2.6.	Statistical optimization	51-53
2.7.	Biooil	53-54
2.8.	Application of biooil	54-56
2.9.	Biochar	56-57
2.10.	Application of biochar	57

2.10.1. Biochar used for removal of heavy metal	58-59
2.10.2. Biochar used for removal of organic pollutants	59-60
References	61-75

Chapter 3: Materials and Methods

3.1. Methodology used	76
3.2. Materials	77
3.2.1. <i>Mesua ferrea</i>	77
3.2.2. <i>Pongamia glabra</i>	77-78
3.2.3. <i>Scenedesmus dimorphus</i>	78
3.3. Proximate analysis	79
3.3.1. Determination of Moisture content	79
3.3.2. Determination of ash content	79-80
3.3.3. Determination of volatile matter	80
3.3.4. Determination of Fixed Carbon	80
3.3.5. Higher heating value (HHV)	80
3.4. Compositional analysis of the lignocellulosic biomass	80
3.4.1. Extractives	81
3.4.2. Lignin	81
3.5. Kinetic modeling	81-83
3.5.1. Friedman method	83
3.5.2. Flynn-Wall-Ozawa or FWO method	83
3.5.3. Kissinger-Akira-Sunnose or KAS method	84
3.6. Pyrolysis experiment	84-86
3.7. Response Surface Methodology (RSM)	86-87
3.8. Fractionation of biooil	87-88
3.9. Instrumental Characterization	88
3.9.1. Elemental characterization	88
3.9.2. TGA analysis	88
3.9.3. FTIR analysis	88

3.9.4.	¹ H NMR	88
3.9.5.	GC-MS	89
3.9.6.	Calorific value	89
3.9.7.	Determination of pH and Electrical Conductivity	89-90
3.9.8.	SEM and EDX analysis	90
3.9.9.	XRD analysis	90
3.9.10.	Carbon sequestration potential	90-91
3.10.	Application of biochar	91
3.10.1.	Adsorption of cobalt (Co) metal by using biochar as adsorbent	91
3.10.2.	Adsorption of cationic dyes by using biochar as adsorbent	91-92
3.11.	Equilibrium study	92
3.11.1.	Langmuir Adsorption Isotherm	92-93
3.11.2.	Freundlich Adsorption Isotherm	93-94
3.11.3.	Temkin Adsorption Isotherm	94-95
3.11.4.	Dubinin–Radushkevich adsorption isotherm	95
3.11.5.	Hurkins-Jura adsorption isotherm	95-96
3.12.	Kinetic Study for adsorption	96
References		97-100

Chapter-4: Results and Discussion

Chapter-4(a): Pyrolysis of *Mesua ferrea* and *Pongamia glabra* seed covers

4-1.1.	Pyrolysis of <i>Mesua ferrea</i> and <i>Pongamia glabra</i> seed covers	101-102
4-1.2.	Physico-chemical characterization of MFSC and PGSC	102-104
4-1.3.	Thermal degradation behavior of PGSC biomass	104-105
4-1.3.1.	Thermo-gravimetric analysis	105-107
4-1.3.2.	Friedman method	107-109
4-1.3.3.	Flynn-Wall-Ozawa (FWO) method	109-110

4-1.3.4.	Kissinger-Akahira-Sunose (KAS) method	110-111
4-1.4.	Thermal degradation behavior of MFSC biomass	111-113
4-1.4.1.	Friedman method	113-114
4-1.4.2.	Flynn-Wall-Ozawa (FWO) method	114-115
4-1.4.3.	Kissinger-Akahira-Sunose (KAS) method	115-116
4-1.5.	Statistical optimization using Response surface model (RSM) for PGSC	117-119
4-1.5.1.	Response surface plots for PGSC	119-121
4-1.5.2.	Optimization of PGSC biooil yield	121-122
4-1.6.	Statistical optimization using Response surface model (RSM) for MFSC	122-124
4-1.6.1.	Response surface plots for MFSC	124-125
4-1.6.2.	Optimization of MFSC biooil yield	125-126
4-1.7.	Pyrolysis of PGSC and MFSC biomass	126
4-1.7.1.	Product yield from PGSC and MFSC	126-129
4-1.7.2.	Yields of column chromatographic fractions of biooils	129
4-1.8.	Characterization of biooil	130
4-1.8.1.	Physical characterization of biooil	130-131
4-1.8.2.	FTIR analysis of biooil	131-134
4-1.8.3.	¹ H NMR analysis of biooil and its sub-fractions	134-136
4-1.8.4.	GC-MS analysis of biooil and their sub-fractions	136-140
4-1.9.	Characterization of biochar	140
4-1.9.1.	Physicochemical characterization of biochar	140-143
4-1.9.2.	Carbon sequestration potential of biochar	143-144
4-1.9.3.	SEM analysis of Biochar	144-146
4-1.9.5.	FTIR analysis of biochar	146-147
4-1.9.6.	XRD analysis of biochar	147-148
4-1.10.	Summary	148-149
	References	150-154

Chapter-4 (b): Pyrolysis of microalgae species *Scenedesmus dimorphus*

4-2.1.	Introduction	155-156
4-2.2.	Physicochemical characterization of <i>S. dimorphus</i>	156-157
4-2.3.	Thermo-gravimetric analysis	157-159
	4-2.3.1. Friedman method	159-161
	4-2.3.2. Flynn-Wall-Ozawa (FWO) method	161-162
	4-2.3.3. Kissinger-Akira-Sunnose (KAS) method	162-163
4-2.4.	Statistical optimization using Response surface model (RSM) for <i>S. dimorphus</i>	163-166
	4-2.4.1. Response surface plots for <i>S. dimorphus</i>	166-168
	4-2.4.2. Optimization of <i>S. dimorphus</i> biooil yield	168
4-2.5.	Pyrolysis of <i>S. dimorphus</i>	168
	4-2.5.1. Sample pyrolysis runs	168-170
	4-2.5.2. Yield of chromatographic fractions	170-171
4-2.6.	Characterization of the liquid product	171
	4-2.6.1. Physical properties of liquid product	171-173
	4-2.6.2. Chemical composition of biooil using FTIR spectra	173-174
	4-2.6.3. ^1H NMR analysis of Biooil	174-176
	4-2.6.4. GC-MS analysis of Biooil	177-179
4-2.7.	Characterization of biochar	180
	4-2.7.1. Physicochemical properties of biochar	180-182
	4-2.7.2. SEM analysis of biochar	182-183
	4-2.7.3. EDX analysis of biochar	183
	4-2.7.4. FTIR analysis of biochar	184-185
	4-2.7.5. Carbon sequestration potential of biochar	185
	4-2.7.6. XRD analysis of biochar	186
4-2.8.	Summary	187-188
	References	189-194

Chapter-4 (c): Biochar utilization as an adsorbent for removal of heavy metal

4-3.1.	Introduction	195
4-3.2.	Cobalt as heavy metal	195-196
4-3.3.	Effect of contact time	196-197
4-3.4.	Equilibrium study	197
4-3.4.1.	Langmuir Adsorption Isotherm	197-199
4-3.4.2.	Freundlich Adsorption Isotherm	199-201
4-3.4.4.	Dubinin–Radushkevich adsorption isotherm	201-202
4-3.4.5.	Harkins-Jura Isotherm (Harkins-Jura adsorption isotherm)	202-204
4-3.5.	Kinetic Study	204-206
4-3.6.	Post sorption characteristics of biochar	206
4-3.6.1.	SEM analysis	206
4-3.6.2.	EDX analysis	207
4-3.7.	Summary	207-208
	References	209-211

Chapter – 4 (d): Biochar utilization as an adsorbent for removal of dye effluents

4-4.1.	Introduction	212
4-4.2.	Selection of dyes	212-213
4-4.3.	Optimization of adsorption parameters	213-214
4-4.4.	Effect of initial concentration	214
4-4.5.	Adsorption isotherm	215-216
4-4.6.	Adsorption kinetics	217-218
4-4.7.	Post sorption characteristics of biochar	218

SEM analysis	218
FTIR analysis	219-220
4-4.8. Summary	220
References	221-223

Chapter – 5: Summary and Conclusions

5.1 Summary	224
5.2. Conclusions	225-228
5.3. Future Scope	228

Appendix

List of Publications

List of Tables

Table no.	Contents	Page no.
Table 1.1	Product weight yields (dry wood basis) obtained by different modes of pyrolysis of wood	16
Table 3.1	GC-MS analyzer details	89
Table 4.1	Physicochemical properties of MFSC and PGSC biomass	103
Table 4.2	Characteristic temperatures for PGSC in active pyrolysis zone (S_{II})	106
Table 4.3	Kinetic parameters obtained from Friedman plot for PGSC	108
Table 4.4	Kinetic parameters obtained from FWO plot for PGSC	109
Table 4.5	Kinetic parameters obtained from KAS plot for PGSC	111
Table 4.6	Characteristic temperatures for MFSC biomass in active pyrolysis zone (S_{II})	113
Table 4.7	Kinetic parameters obtained from Friedman plot for MFSC	114
Table 4.8	Kinetic parameters obtained from FWO plot for MFSC	115
Table 4.9	Kinetic parameters obtained from KAS plot for MFSC	116
Table 4.10	Design matrix using Central Composite Design and experiment results	117
Table 4.11	Results of ANOVA for PGSC	118
Table 4.12	Design matrix using Central Composite Design and experiment results	122
Table 4.13	Results of ANOVA for MFSC	123
Table 4.14	Product distribution of both PGSC and MFSC biomass	127
Table 4.15	Physico-chemical properties of biooil and its comparison with petro-fuels	131
Table 4.16	Percentage of hydrogen based on 1H NMR analysis of PGSC and MFSC biooil sub-fractions	134
Table 4.17	Chemical compounds in PGSC and MFSC biooils and their corresponding n-hexane fractions (GC-MS)	139

Table no.	Contents	Page no.
Table 4.18	Various properties of biochar co-produced from pyrolysis of PGSC and MFSC samples	140
Table 4.19	R_{50} index and CSP values of biochars obtained at different temperatures for both PGSC and MFSC samples and a comparison with R_{50} index of other biochars	143
Table 4.20	Elemental composition of MFSC biochar produced at 550 °C obtained from EDX analysis	145
Table 4.21	Elemental composition of PGSC biochar produced at 550 °C obtained from EDX analysis	146
Table 4.22	Physicochemical properties of <i>S. dimorphus</i> biomass	156
Table 4.23	Characteristic temperatures for <i>S. dimorphus</i> in active pyrolysis zone (S_{II})	159
Table 4.24	Kinetic parameters obtained from the Friedman plot for <i>S. dimorphus</i>	160
Table 4.25	Kinetic parameters obtained from the FWO plot for <i>S. dimorphus</i>	161
Table 4.26	Kinetic parameters obtained from the KAS plot for <i>S. dimorphus</i>	162
Table 4.27	Design matrix using Central Composite Design and experiment results	164
Table 4.28	Results of ANOVA for <i>S. dimorphus</i>	165
Table 4.29	Pyrolysis product distribution of <i>S. dimorphus</i> at different temperatures	169
Table 4.30	Physicochemical properties of biooil obtained from <i>S. dimorphus</i> at 500 °C with 40 °C/min heating rate and their comparison with petro fuels	172
Table 4.31	Percentage of hydrogen based on ^1H NMR analysis of microalgae biooil sub-fractions.	175

Table 4.32	Retention time (in min) and compound name present in microalgae biooil and its corresponding fractions obtained from GC-MS analysis	178
Table no.	Contents	Page no.
Table 4.33	Properties of biochars obtained at different temperatures from pyrolysis <i>S. dimorphus</i>	180
Table 4.34	Elemental composition of <i>S. dimorphus</i> biochar from EDX analysis	183
Table 4.35	R ₅₀ index and CSP of <i>S. dimorphus</i> biochars at different temperatures	185
Table 4.36	Langmuir adsorption isotherm parameters	198
Table 4.37	Freundlich adsorption isotherm parameters	200
Table 4.38	D-R adsorption isotherm parameters	202
Table 4.39	Hurkins-Jura adsorption isotherm parameters	203
Table 4.40	Kinetic parameters derived from both Pseudo first-order and pseudo second-order reaction models for adsorption of Co (II) on biochar surfaces	204
Table 4.41	Isotherm constants for the adsorption of MB and RB with PGSC biochar	216
Table 4.42	Pseudo-second-order kinetics parameters for adsorption of MB and RB on PGSC biochar	218

List of Figures

Fig. no.	Contents	Page no.
Fig. 1.1	Various resources of biomass	5
Fig. 1.2	Classification of biofuels	10
Fig. 1.3	Various biomass conversion technologies	12
Fig. 1.4	Scheme of cellulose pyrolysis mechanism	24
Fig. 3.1	Flowchart of methodology adopted for the present study	76
Fig. 3.2	<i>Mesua ferrea</i> seed and seed cover	77
Fig. 3.3	<i>Pongamia glabra</i> seed and seed cover	78
Fig. 3.4	Dried <i>Scenedesmus dimorphus</i>	78
Fig. 3.5	Schematic (a) and pictorial (b) diagram of pyrolysis experimental setup	85
Fig. 3.6	Separation of Pyrolytic liquid	86
Fig. 4.1	TG curves of PGSC recorded at three different heating rates	106
Fig. 4.2	DTG curves of PGSC recorded at three different heating rates	106
Fig. 4.3	Plots obtained by Friedman method for determination of activation energy of PGSC at S_{II}	108
Fig. 4.4	Plots obtained by FWO method for determination of activation energy of PGSC at S_{II}	109
Fig. 4.5	Plots obtained by KAS method for determination of activation energy of PGSC at S_{II}	110
Fig. 4.6	TG curves of MFSC biomass recorded at three different heating rates	112
Fig. 4.7	DTG curves of MFSC biomass recorded at three different heating rates	112
Fig. 4.8	Plots obtained by Friedman method for determination of activation energy of MFSC at S_{II}	114
Fig. 4.9	Plots obtained by FWO method for determination of activation energy of MFSC at S_{II}	115
Fig. 4.10	Plots obtained by KAS method for determination of activation energy of MFSC at S_{II}	116

Fig. no.	Contents	Page no.
Fig. 4.11	Response surface plots and contour plots of yield percentage of biooil (a, b); biochar (c, d); and gas (e, f) obtained from pyrolysis of PGSC	119-120
Fig. 4.12	Optimum conditions for highest yield of liquid product from pyrolysis of PGSC	121
Fig. 4.13	Response surface plots and contour plots of yield percentage of biooil (a, b); biochar (c, d); and gas (e, f) obtained from pyrolysis of MFSC	124-125
Fig. 4.14	Optimum conditions for highest yield of liquid product from pyrolysis of MFSC	126
Fig. 4.15	(a) Effect of temperature on solid, liquid and gaseous products of PGSC biomass	127
Fig. 4.15	(b) Effect of temperature on solid, liquid and gaseous products of MFSC biomass	127
Fig. 4.16	Yields of column chromatographic sub-fractions obtained from PGSC & MFSC biooils	129
Fig. 4.17	FTIR spectra of (a) MFSC and (b) PGSC biooil	131
Fig. 4.18	FTIR images of sub-fractions obtained from PGSC biooil after elution of using solvents (a) n-hexane, (b) toluene, (c) ethyl-acetate, and (d) methanol	132
Fig. 4.19	FTIR images of sub-fractions obtained from MFSC biooil after elution of using solvents (a) n-hexane, (b) toluene, (c) ethyl-acetate, and (d) methanol	133
Fig. 4.20	TIC of PGSC biooil	137
Fig. 4.21	TIC of n-hexane fraction of PGSC biooil	137
Fig. 4.22	TIC of MFSC biooil	137
Fig. 4.23	TIC of n-hexane fraction of MFSC biooil	138
Fig. 4.24	Van Krevelen diagram of (a) PGSC and (b) MFSC biochars obtained at different temperatures.	142

Fig. no.	Contents	Page no.
Fig. 4.25	SEM images of MFSC biochars obtained at (a) 350 °C (b) 450 °C and (c) 550 °C	144
Fig. 4.26	SEM images of PGSC biochars obtained at (a) 350 °C (b) 450 °C and (c) 550 °C	145
Fig. 4.27	EDX spectrum of MFSC biochar produced at 550 °C	145
Fig. 4.28	EDX spectrum of PGSC biochar produced at 550 °C	146
Fig. 4.29	FTIR of (a) PGSC and (b) MFSC biochar obtained at different temperatures	146
Fig. 4.30	XRD patterns of biochars obtained at different temperatures for (a) PGSC and (b) MFSC biomass	148
Fig. 4.31	TG of weight loss curves of <i>S. dimorphus</i> recorded at three heating rates.	158
Fig. 4.32	DTG curves of <i>S. dimorphus</i> biomass recorded at three different heating rates	158
Fig. 4.33	Plots obtained by Friedman method for determination of activation energy of <i>S. dimorphus</i> at S _{II}	160
Fig. 4.34	Plots obtained by FWO method for determination of activation energy of <i>S. dimorphus</i> at S _{II}	161
Fig. 4.35	Plots obtained by KAS method for determination of activation energy of <i>S. dimorphus</i> at S _{II}	162
Fig. 4.36	Response surface plots and contour plots of yield percentage of biooil (a, b); biochar (c, d); and gas (e, f) obtained from pyrolysis of <i>S. dimorphus</i>	166-167
Fig. 4.37	Optimum conditions for highest yield of liquid product from pyrolysis of <i>S. dimorphus</i>	168
Fig. 4.38	Pyrolysis product yield of <i>S. dimorphus</i> at different temperatures	169
Fig. 4.39	Yield percentage of sub-fractions from <i>S. dimorphus</i> biooil	171
Fig. 4.40	FTIR images of sub-fractions obtained from <i>S. dimorphus</i> biooil after elution of using solvents (a) n-hexane, (b) toluene, (c) ethyl-acetate, and (d) methanol	173
Fig. 4.41	TIC of microalgae biooil	177

Fig. no.	Contents	Page no.
Fig. 4.42	TIC of n-hexane fraction of microalgae biooil	177
Fig. 4.43	Van-kravelen diagram of biochars obtained from <i>S. dimorphous</i>	182
Fig. 4.44	SEM images of biochars produced at (a) 300 °C, (b) 400 °C, and (c) 500 °C	182
Fig. 4.45	EDX spectrum of biochar produced at 500 °C from <i>S. dimorphous</i>	183
Fig. 4.46	FTIR spectra of <i>S. dimorphous</i> biochar produced at different temperatures	184
Fig. 4.47	XRD analysis of <i>S. dimorphous</i> biochar obtained at different temperatures	186
Fig. 4.48	Effect of contact time on removal of Co (II) by using biochars derived from PGSC, MFSC and <i>S. dimorphous</i>	196
Fig. 4.49	Langmuir adsorption isotherms for (a) PGSC, (b) MFSC and (c) <i>S. dimorphous</i>	198
Fig. 4.50	Freundlich adsorption isotherms for (a) PGSC, (b) MFSC and (c) <i>S. dimorphous</i>	200
Fig. 4.51	D-R adsorption isotherms for (a) PGSC, (b) MFSC and (c) <i>S. dimorphous</i>	202
Fig. 4.52	Hurkins-Jura adsorption isotherms for (a) PGSC, (b) MFSC and (c) <i>S. dimorphous</i>	203
Fig. 4.53	Pseudo first-order (a) and pseudo-second-order (b) reaction models for PGSC biochar	205
Fig. 4.54	Pseudo first-order (a) and pseudo-second-order (b) reaction models for MFSC biochar	205
Fig. 4.55	Pseudo first-order (a) and pseudo-second-order (b) reaction models for <i>S. dimorphous</i> biochar	206
Fig. 4.56	SEM images of biochars derived from (a) PGSC, (b) MFSC and (c) <i>S. dimorphous</i> after adsorption Co (II)	206
Fig. 4.57	EDX spectrum of biochars after adsorption of Co (II) derived from (a) PGSC (b) MFSC and (c) <i>S. dimorphous</i>	207

Fig. no.	Contents	Page no.
Fig. 4.58	Plots showing optimization of (a) biomass, (b) pH and (c) temperature for the adsorption of Methylene blue (MB) and Rhodamine B (RB) by PGSC biochar	214
Fig. 4.59	Effect of initial concentration on uptake of (a) Methylene blue (MB) and (b) Rhodamine B (RB) by PGSC biochar	215
Fig. 4.60	Isotherm plots for adsorption of (a) Methylene blue (MB) and (b) Rhodamine B (RB) by PGSC biochar	215
Fig. 4.61	Pseudo-second-order sorption plots for adsorption of (a) Methylene blue (MB) and (b) Rhodamine B (RB) on PGSC biochar.	217
Fig. 4.62	SEM image of PGSC biochar (a) before dye adsorption (b) after adsorption of Methylene blue (MB) and (c) after adsorption of Rhodamine B (RB)	218
Fig. 4.63	FTIR spectrum of PGSC biochar before (black) and after adsorption with MB (blue) and RB (red).	220

List of Abbreviations

TGA	Thermogravimetric analysis
DTG	Differential thermogravimetry
MFSC	<i>Mesua ferrea</i> seed cover
PGSC	<i>Pongamia glabra</i> seed cover
FWO	Flynn-Wall-Ozawa
KAS	Kissinger-Akahira-Sunose
RSM	Response surface methodology
CCD	Central composite design
ANOVA	Analysis of variance
GC-MS	Gas chromatography-Mass spectrometry
TIC	Total ion chromatogram
FTIR	Fourier transformed infrared
GHG	Greenhouse gas
SEM	Scanning electron microscope
S _I	Initial degradation stage of a DTG curve
S _{II}	Active pyrolysis zone
S _{III}	Passive pyrolysis zone
T _{end}	Ending temperature of a particular zone of active pyrolysis
T _{max}	Temperature where maximum mass loss rate occur
T _{onset}	Starting temperature of a particular zone of active pyrolysis
W _{max}	Maximum mass loss rate
XRD	X-ray diffraction
EDX	Energy dispersive x-ray spectroscopy
L	Liter