

List of Figures

Chapter 1

Fig. 1.1: (a) Schematic view of a Double-gate Junctionless Transistor (b) Direction of Electric fields due to work function difference (E_{wfd}) and applied gate voltage (E_{gs})

Fig. 1.2: JLT in Subthreshold mode (a) Schematic view (b) Direction of resultant electric field ($E_{resultant}$)

Fig. 1.3: JLT in Bulk Current Mode (a) Schematic view (b) Direction of resultant electric field ($E_{resultant}$)

Fig. 1.4: JLT in Flat band Mode (a) Schematic view (b) Direction of resultant electric field ($E_{resultant}$)

Fig. 1.5: JLT in Accumulation Mode (a) Schematic view (b) Direction of resultant electric field ($E_{resultant}$)

Fig. 1.6: Transfer characteristics of a JLT showing different modes of operation

Chapter 2

Fig. 2.1: A Bulk MOSFET

Fig. 2.2: Cross-sectional view of (A) Fully Depleted SOI MOSFET and (B) Partially Depleted SOI MOSFET

Fig. 2.3: Cross-sectional view of an SOI MOSFET showing floating body effect

Fig. 2.4: Output characteristics of an SOI MOSFET showing Kink effect

Fig. 2.5: Punch-through

Fig. 2.6: DIBL

Fig. 2.7: Channel length modulation

Fig. 2.8: Formation of a depletion layer in the drain

Fig. 2.9: Gate oxide leakage

Fig. 2.10: Band diagram for F-N tunnelling

Fig. 2.11: Charge sharing effect

Fig. 2.12: Hot carrier effect

Fig. 2.13: Cross-sectional view of Double Gate SOI MOSFET

Fig. 2.14: FinFET typical layout and schematic cross sectional structures

Fig. 2.15: Schematic of a triple-gate SOI transistor

Fig. 2.16: CYNTHIA/surrounding-gate MOSFET structure

Fig. 2.17: Evolution of MOSFET from Conventional MOSFET to Junctionless Transistor

Fig. 2.18: Drain current as a function of gate voltage in (a) Inversion Mode MOSFET (“n⁺pn⁺” doped) (b) Accumulation mode MOSFET (“n⁺m⁺” doped) (c) A heavily doped Junctionless Transistor (“n⁺n⁺n⁺” doped)

Chapter 3

Fig. 3.1: Cross sectional view of a Gate all around (pentagonal cross section) JLT

Fig. 3.2: Cross sectional view of a Gate all around (hexagonal cross section) JLT

- Fig. 3.3: Cross sectional view of a Gate all around (octagonal cross section) JLT
- Fig. 3.4: Cross sectional view of a Gate all around (rectangular cross section) JLT
- Fig. 3.5: Scale length variation with gate oxide thickness
- Fig. 3.6: Scale length variation with side length
- Fig. 3.7: Scale length variation with width to thickness ratio rectangular JLT keeping constant cross sectional area
- Fig. 3.8: Scale length variation with dielectric constant of gate dielectric
- Fig. 3.9: Transverse potential profile for different value of drain to source voltage for (a) Pentagonal (b) Hexagonal (c) Octagonal (d) Rectangular JLT
- Fig. 3.10: Transverse potential profile for different value of gate oxide thickness for (a) Pentagonal (b) Hexagonal (c) Octagonal (d) Rectangular JLT
- Fig. 3.11: Transverse potential profile for different value of channel length for (a) Pentagonal (b) Hexagonal (c) Octagonal (d) Rectangular JLT
- Fig. 3.12: Transverse potential profile for different value of gate to source voltage for (a) Pentagonal (b) Hexagonal (c) Octagonal (d) Rectangular JLT
- Fig. 3.13: Central potential profile for different value of drain to source voltage for (a) Pentagonal (b) Hexagonal (c) Octagonal (d) Rectangular JLT
- Fig. 3.14: Central potential profile for different value of gate oxide thickness for (a) Pentagonal (b) Hexagonal (c) Octagonal (d) Rectangular JLT
- Fig. 3.15: Central potential profile for different value of gate to source voltage for (a) Pentagonal (b) Hexagonal (c) Octagonal (d) Rectangular JLT

Chapter 4

Fig. 4.1: Single Gate JLT

Fig. 4.2: Double Gate JLT

Fig. 4.3: Depletion Width variation with doping concentration for n-channel single gate and double gate JLT

Fig. 4.4: Depletion Width variation with doping concentration for p-channel single gate and double gate JLT

Fig. 4.5: Depletion Width variation with drain to source voltage for n-channel single gate and double gate JLT

Fig. 4.6: Depletion Width variation with drain to source voltage for p-channel single gate and double gate JLT

Fig. 4.7: Depletion Width variation with gate to source voltage for n-channel single gate and double gate JLT

Fig. 4.8: Depletion Width variation with gate to source voltage for p-channel single gate and double gate JLT

Fig. 4.9: Depletion Width variation with dielectric constant of gate dielectric for n-channel single gate and double gate JLT

Fig. 4.10: Depletion Width variation with dielectric constant of gate dielectric for p-channel single gate and double gate JLT

Fig. 4.11: Variation of Threshold voltage with Drain Voltage

Fig. 4.12: Variation of Threshold voltage with Channel Length (short channel)

- Fig. 4.13: Variation of Threshold voltage with Channel Length (long channel)
- Fig. 4.14: Variation of Threshold voltage with Doping Concentration
- Fig. 4.15: Variation of Threshold voltage with Channel Thickness
- Fig. 4.16: Variation of Threshold voltage with Gate Oxide Thickness
- Fig. 4.17: Cross sectional view of a tri-gate JLT
- Fig. 4.18: Scale length variation with Silicon layer thickness for the dielectrics SiO₂ (3.9), Al₂O₃ (10) and HfO₂ (22) at $t_{ox} = 2\text{nm}$
- Fig. 4.19: Scale length variation with Gate Oxide thickness at $t_{Si} = 10\text{nm}$
- Fig. 4.20: Longitudinal Potential variation of DG JLT for $V_{gs} = 0V, 0.25V$ and $0.5V, y = 0$
- Fig. 4.21: Longitudinal Potential variation of DG JLT for $V_{ds} = 0V, 1V$ and $2V, y = 0$
- Fig. 4.22: Longitudinal Potential variation of DG JLT for $t_{ox} = 2\text{nm}, 4\text{nm}$ and $6\text{nm}, y = 0$
- Fig. 4.23: Longitudinal Potential variation of DG JLT for $t_{Si} = 5\text{nm}, 10\text{nm}$ and $15\text{nm}, y = 0$
- Fig. 4.24: Longitudinal Potential variation of DG JLT for $L = 20\text{nm}, 50\text{nm}$ and $100\text{nm}, y = 0$
- Fig. 4.25: Longitudinal Potential variation of DG JLT for $L_s = L_d = 5\text{nm}, 10\text{nm}$ and $20\text{nm}, y = 0$
- Fig. 4.26: Transverse Potential variation of DG JLT for $V_{ds} = 0V, 1V$ and $2V, x = \frac{L}{2}$

Fig. 4.27: Transverse Potential variation of DG JLT for $V_{gs} = 0V, 0.1V$ and $0.2V$, $x = \frac{L}{2}$

Fig. 4.28: Transverse Potential variation of DG JLT for $t_{ox} = 2nm, 4nm$ and $6nm$, $x = \frac{L}{2}$

Fig. 4.29: Transverse Potential variation of DG JLT for $L = 20nm, 50nm$ and $100nm$,
 $x = \frac{L}{2}$

Fig. 4.30: Transverse Potential variation of DG JLT for $t_{si} = 5nm, 10nm$ and $15nm$, $x = \frac{L}{2}$

Fig. 4.31: Longitudinal potential variation with channel position along x- direction at $y=0$ for $V_{gs}=0V, 0.3V$ and $0.6V$ for tri-gate JLT.

Fig. 4.32: Longitudinal potential variation with channel position along x- direction at $y=0$ for $t_{ox}=2nm, 3nm$ and $4nm$ for tri-gate JLT.

Fig. 4.33: Longitudinal potential variation with channel position along x- direction at $y=0$ for $V_{ds}=0.1V, 0.3V$ and $0.5V$ for tri-gate JLT.

Fig. 4.34: Transverse potential variation with channel position along y-direction at $x=L/2$ for $V_{gs}=0V, 0.3V$ and $0.6V$

Fig. 4.35: Transverse potential variation with channel position along y-direction at $x=L/2$ for $t_{ox}=2nm, 3nm$ and $4nm$ for tri-gate JLT.

Fig. 4.36: Transverse potential variation with channel position along y-direction at $x=L/2$ for $V_{ds}=0.1V, 0.3V$ and $0.5V$ for tri-gate JLT.

Fig. 4.37: Comparison of potential model with experimental results

Chapter 5

- Fig. 5.1: Cross sectional view of a Double Gate JLT
- Fig. 5.2: A Double Gate JLT with body divided into a number of small segments of length ΔL
- Fig. 5.3: Equivalent circuit of a segment (a) A segment with combination of depletion and neutral semiconductor region (b) A non depleted segment (c) A fully depleted segment
- Fig. 5.4: Transfer characteristics for different value of channel length
- Fig. 5.5: Transfer characteristics for different value of channel length (linear scale)
- Fig. 5.6: Output characteristics for different value of channel length
- Fig. 5.7: Transfer characteristics for different value of Gate oxide thickness
- Fig. 5.8: Output characteristics for different value of Gate oxide thickness
- Fig. 5.9: Transfer characteristics for different value of channel thickness
- Fig. 5.10: Output characteristics for different value of channel thickness
- Fig. 5.11: Transfer characteristics for different value of Drain to source voltage
- Fig. 5.12: Transfer characteristics for different value of Drain to source voltage (linear scale)
- Fig. 5.13: Output characteristics for different value of Gate to source voltage
- Fig. 5.14: Variation of Drain resistance with drain voltage

Fig. 5.15: Transconductance variation with gate voltage for different values of channel length

Fig. 5.16: Transconductance variation with gate voltage for different values of drain voltage

Fig. 5.17: Outputconductance variation with drain voltage for different values of gate voltage

Fig. 5.18: Outputconductance variation with drain voltage for different values of channel length

Fig. 5.19: Transfer characteristics comparison with experimental value

Fig. 5.20: Output characteristics comparison with experimental value

Chapter 6

Fig. 6.1: Variation Minimum Possible Gate Oxide Thickness with Channel Thickness

Fig. 6.2: Variation Minimum Possible Scale Length with Channel Thickness

Fig. 6.3: Variation Minimum Gate Length with Channel Thickness

Fig. 6.4: Cross sectional view of a double gate JLT with dielectric at channel centre

Fig. 6.5: 3-D view of a double gate JLT with dielectric at channel centre showing segmentation

Fig. 6.6: (a) Equivalent circuit of a segment (b) Cross sectional view one segment

Fig. 6.7: Transfer Characteristic Comparison for different centre dielectric thickness

Fig. 6.8: Transfer Characteristic Comparison for different dielectric constant value of centre dielectric

- Fig. 6.9: Transfer Characteristic Comparison for different centre dielectric length
- Fig. 6.10: Transfer Characteristic Comparison of conventional JLT and JLT with centre dielectric layer with same effective channel area
- Fig. 6.11: Cross sectional view of a Symmetric DG JLT with two dielectrics diagonally placed
- Fig. 6.12: Cross sectional view of a Asymmetric DG JLT with two dielectrics diagonally placed
- Fig. 6.13: Cross sectional view of a DG JLT with gradual variation of doping concentration in the channel
- Fig. 6.14: Doping profile of the DG JLT with gradual variation of doping concentration
- Fig. 6.15: Longitudinal electric field variation with channel position along x direction (subthreshold region)
- Fig. 6.16: Transverse electric field variation with channel position along y direction (subthreshold region)
- Fig. 6.17: Electron mobility variation with channel position along x direction (subthreshold region)
- Fig. 6.18: Hole mobility variation with channel position along x direction (subthreshold region)
- Fig. 6.19: Electron mobility variation with channel position along y direction (subthreshold region)
- Fig. 6.20: Hole mobility variation with channel position along y direction (subthreshold region)

- Fig. 6.21: Longitudinal electric field variation with channel position along x direction (on state)
- Fig. 6.22: Transverse electric field variation with channel position along y direction (on state)
- Fig. 6.23: Electron mobility variation with channel position along x direction (on state)
- Fig. 6.24: Hole mobility variation with channel position along x direction (on state)
- Fig. 6.25: Electron mobility variation with channel position along y direction (on state)
- Fig. 6.26: Hole mobility variation with channel position along y direction (on state)
- Fig. 6.27: Transfer Characteristics Comparison with SiO₂ as the dielectric for Gradual channel doping variation
- Fig. 6.28: Transfer Characteristics Comparison with HfO₂ as the dielectric for Gradual channel doping variation
- Fig. 6.29: CMOS Inverter Using JLT
- Fig. 6.30: Voltage Transfer Characteristics of Inverter
- Fig. 6.31: Voltage Transfer Characteristics for $V_{dd}=2V$
- Fig. 6.32: Voltage Transfer Characteristics for $V_{dd}=1.5V$
- Fig. 6.33: Voltage Transfer Characteristics for $V_{dd}=1V$
- Fig. 6.34: Rail to Rail Current Variation with Input Voltage for $V_{dd}=2V$
- Fig. 6.35: Rail to Rail Current Variation with Input Voltage for $V_{dd}=1.5V$
- Fig. 6.36: Rail to Rail Current Variation with Input Voltage for $V_{dd}=1V$

- Fig. 6.37: Transient Response for $V_{dd}=2V$
- Fig. 6.38: Transient Response for $V_{dd}=1.5V$
- Fig. 6.39: Transient Response for $V_{dd}=1V$
- Fig. 6.40: Power Loss Variation with Input Voltage at $V_{dd}=2V$
- Fig. 6.41: Power Loss Variation with Input Voltage at $V_{dd}=1.5V$
- Fig. 6.42: Power Loss Variation with Input Voltage at $V_{dd}=1V$
- Fig. 6.43: Transient Response Along with Power Loss at $V_{dd}=2V$
- Fig. 6.44: Transient Response Along with Power Loss at $V_{dd}=1.5V$
- Fig. 6.45: Transient Response Along with Power Loss at $V_{dd}=1V$
- Fig. 6.46: Cross-sectional view of a rectangular JLT with lateral gate underlap
- Fig. 6.47: Cross-sectional view of a pentagonal JLT with lateral gate underlap
- Fig. 6.48: Cross-sectional view of a hexagonal JLT with lateral gate underlap
- Fig. 6.49: Cross-sectional view of a octagonal JLT with lateral gate underlap
- Fig. 6.50: Electric field variation with channel position for rectangular, pentagonal, hexagonal and octagonal JLT
- Fig. 6.51: Comparison of electric field variation with channel position for rectangular JLT with and without gate underlap
- Fig. 6.52: Comparison of electric field variation with channel position for pentagonal JLT with and without gate underlap

- Fig. 6.53: Comparison of electric field variation with channel position for hexagonal JLT with and without gate underlap
- Fig. 6.54: Comparison of electric field variation with channel position for octagonal JLT with and without gate underlap
- Fig. 6.55: Comparison of output characteristics for rectangular JLT with and without gate underlap
- Fig. 6.56: Comparison of output characteristics for pentagonal JLT with and without gate underlap
- Fig. 6.57: Comparison of output characteristics for hexagonal JLT with and without gate underlap
- Fig. 6.58: Comparison of output characteristics for octagonal JLT with and without gate underlap
- Fig. 6.59: Comparison of transfer characteristics for rectangular JLT with and without gate underlap
- Fig. 6.60: Comparison of transfer characteristics for pentagonal JLT with and without gate underlap
- Fig. 6.61: Comparison of transfer characteristics for hexagonal JLT with and without gate underlap
- Fig. 6.62: Comparison of transfer characteristics for octagonal JLT with and without gate underlap