

List of Tables

Table	Caption	Page No.
Table 2.1	The value of heterogeneous rate constant (k_s) derived for different electron transfer processes	56
Table 3.1	Some physical properties of the materials used in synthesis	63-64
Table 4.1	The calculated value of R_{ct} , C_{dl} and Φ for the modified electrodes	92
Table 4.2	The values of peak current (I_{pa} and I_{pc}) and peak to peak ΔE_p	96
Table 4.3	The value of slopes of the regression equation of the linear plot of peak current vs. square root of scan rate ($v^{1/2}$).	99
Table 4.4	The calculated values of electro active surface area	99
Table 4.5	The calculated values of surface concentration of anti-AFB ₁ and AChE immobilized in PEDOT/GCE and AuNPs/PEDOT/GCE, respectively	100
Table 4.6	The calculated values of heterogenous rate transfer constant (k_s) and transfer coefficient (α)	101
Table 4.7	Analytical Parameters of BSA/anti-AFB ₁ /AuNPs/PEDOT/GCE towards the detection of AFB ₁	107
Table 4.8	Statistics and performance characteristics of the Working electrodes towards standard AFB ₁ sample	108
Table 4.9	Statistics and performance characteristics of the Working electrodes towards standard AFB ₁ sample	109
Table 4.10	Analytical parameters of AChE/AuNPs/PEDOT/GCE towards Methyl parathion inhibition.	117
Table 5.1	The calculated value of R_{ct} , C_{dl} and Φ for the modified electrodes	128
Table 5.2	The parameters of cyclic voltammogram (I_{pa} and I_{pc} and	131

	ΔE_p) for the modified electrodes.	
Table 5.3	The value of cathodic and anodic slope and regression coefficient for variation of I_{pa} and I_{pc} with $v^{1/2}$	133
Table 5.4	The calculated values of electro active surface area of modified electrodes	134
Table 5.5	The value of ionic species after immobilization anti-AFB ₁ and AChE	135
Table 5.6	The calculated values of heterogenous rate transfer constant (k_s) and transfer coefficient (α)	137
Table 5.7	Analytical Parameters of the fabricated electrode towards the detection of AFB ₁ in PBS and maize matrix.	143
Table 5.8	Statistics and performance characteristics of the Working electrodes towards standard AFB ₁ sample.	144
Table 5.9	Statistics and performance characteristics of the Working electrodes towards spiked AFB ₁ sample.	145
Table 5.10	Analytical parameters of AChE/AuNPs/PEDOT-GO/GCE towards the detection of MP.	150
Table 6.1	The calculated value of R_{et} , C_{dl} and Φ for the modified electrodes	161
Table 6.2	The parameters of cyclic voltammogram (I_{pa} and I_{pc} and ΔE_p) for the modified electrodes.	163
Table 6.3	The value of slope y-intercept and regression coefficient for variation of I_{pa} and I_{pc} with $v^{1/2}$	166
Table 6.4	The calculated values of electro active surface area of modified electrodes	166
Table 6.5	The value of ionic species after immobilization anti-AFB ₁ and AChE	167
Table 6.6	The calculated values of heterogeneous rate transfer constant (k_s) and transfer coefficient (α)	170
Table 6.7	Analytical Parameters of the fabricated electrode towards the detection of AFB ₁ in PBS and maize matrix	176

Table 6.8	Statistics and performance characteristics of BSA/anti-AFB ₁ /PEDOT-PSS-fMWCNTs/GCE towards standard AFB ₁ sample	177
Table 6.9	Statistics and performance characteristics of the Working electrodes towards standard AFB ₁ sample	178
Table 6.10	Analytical parameters of AChE/PEDOT-PSS-fMWCNTs/GCE towards the detection of Methyl parathion and Carbofuran	187
Table 6.11	Statistics and performance characteristics of the AChE/PEDOT-PSS-fMWCNTs/GCE towards soil water sample spiked with pesticide sample	190
Table 6.12	Statistics and performance characteristics of the AChE/AuNPs/PEDOT-GO/GCE towards green tea water sample spiked with pesticide sample	191