

# Bibliography

- [1] The effect of silane coupling agents on radiata pine fibre for use in thermo-plastic matrix composites.
- [2] Assessment of utilization of industrial solid wastes in cement manufacturing, Programme objective series PROBES/103/2006-2007, Central Pollution Control Board (Govt. of India). Technical report, 2006.
- [3] Surface properties of natural calcite filler treated with stearic acid, author=Slavica Mihajlović and Živko Sekulić and Aleksandra Daković and Dušica Vučinić and Vladimir Jovanović and Jovica Stojanović. *Ceramic Si-likaty*, 53(4):268–275, 2009.
- [4] Utilization of lime sludge for value added products and productivity enhancement of lime kilns, Report No. CRI-ENG-SP 965, National Council for Cement and Building Materials (India). Technical report, March 2000.
- [5] Abdulmajeed, A. A., Närhi, T. O., Vallittu, P. K., and Lassila, L. V. The effect of high fiber fraction on some mechanical properties of unidirectional glass fiber-reinforced composite. *Dental Materials*, 27(4):313–321, 2011.
- [6] Acha, B. A., Aranguren, M. I., Marcovich, N. E., and Reboredo, M. M. Composites from PMMA modified thermosets and chemically treated woodflour. *Polymer Engineering & Science*, 43(5):999–1010, 2003.
- [7] Adams, J. Particle size and shape effects in materials science: examples from polymer and paper systems. *Clay Minerals*, 28(4):509–530, 1993.
- [8] Agrawal, A. and Satapathy, A. Development of a heat conduction model and investigation on thermal conductivity enhancement of AlN/epoxy composites. *Procedia Engineering*, 51:573–578, 2013.
- [9] Ahmad, T., Ahmad, R., Kamran, M., Wahjoedi, B., Shakoor, I., Hussain, F., Riaz, F., Jamil, Z., Isaac, S., and Ashraf, Q. Effect of Thal silica sand nanoparticles and glass fiber reinforcements on epoxy-based hybrid composite. *Iranian Polymer Journal*, 24(1):21–27, 2015.
- [10] Ahmadi, B. and Al-Khaja, W. Utilization of paper waste sludge in the building construction industry. *Resources, conservation and recycling*, 32(2):105–113, 2001.

- [11] Ahmetli, G., Kocak, N., Dag, M., and Kurbanli, R. Mechanical and thermal studies on epoxy toluene oligomer-modified epoxy resin/marble waste composites. *Polymer Composites*, 33(8):1455–1463, 2012.
- [12] Akinci, A., Akbulut, H., and Yilmaz, F. Mechanical properties of cost-effective polypropylene composites filled with red-mud particles. *Polymers & Polymer Composites*, 16(7):439, 2008.
- [13] Alamri, H. and Low, I. M. Mechanical properties and water absorption behaviour of recycled cellulose fibre reinforced epoxy composites. *Polymer testing*, 31(5):620–628, 2012.
- [14] Aldousiri, B., Alajmi, M., and Shalwan, A. Mechanical properties of palm fibre reinforced recycled HDPE. *Advances in Materials Science and Engineering*, 2013, 2013.
- [15] Ansarifar, A., Osmani, M., Wang, L., Yoonga, K. K., and Pappu, A. Characterisation and use of glass fibre reinforced plastic waste Powder as filler in styrene-butadiene rubber. *Journal of Rubber Research*, 13(3):162–174, 2010.
- [16] Araujo, J. R., Waldman, W. R., and Paoli, M. A. D. Thermal properties of high density polyethylene composites with natural fibres: Coupling agent effect. *Polymer degradation and stability*, 93(10):1770–1775, 2008.
- [17] Asaad, J. N. and Tawfik, S. Y. Polymeric composites based on polystyrene and cement dust wastes. *Materials & Design*, 32(10):5113–5119, 2011.
- [18] Asokan, P., Osmani, M., and Price, A. D. F. Improvement of the mechanical properties of glass fibre reinforced plastic waste powder filled concrete. *Construction and Building Materials*, 24(4):448–460, 2010.
- [19] Athijayamani, A., Thiruchitrambalam, M., Natarajan, U., and Pazhanivel, B. Effect of moisture absorption on the mechanical properties of randomly oriented natural fibers/polyester hybrid composite. *Materials Science and Engineering: A*, 517(1-2):344–353, 2009.
- [20] Atikler, U., Basalp, D., and Tihminlioğlu, F. Mechanical and morphological properties of recycled high-density polyethylene, filled with calcium carbonate and fly ash. *Journal of applied polymer science*, 102(5):4460–4467, 2006.
- [21] Avella, M., Bogoeva-Gaceva, G., Bužarovska, A., Errico, M. E., Gentile, G., and Grozdanov, A. Poly (lactic acid)-based biocomposites reinforced with kenaf fibers. *Journal of applied polymer science*, 108(6):3542–3551, 2008.
- [22] Ayrimis, N., Jarusombuti, S., Fueangvivat, V., Bauchongkol, P., and White, R. H. Coir fiber reinforced polypropylene composite panel for automotive interior applications. *Fibers and Polymers*, 12(7):919, 2011.
- [23] Aziz, S. H., Ansell, M. P., Clarke, S. J., and Panteny, S. R. Modified polyester resins for natural fibre composites. *Composites Science and Technology*, 65(3): 525–535, 2005.

- [24] Badran, B. M., Galski, A., and Kryszewski, M. High-density polyethylene filled with modified chalk. *Journal of Applied Polymer Science*, 27(10):3669–3681, 1982.
- [25] Bajracharya, R. M., Bajwa, D. S., and Bajwa, S. G. Mechanical properties of polylactic acid composites reinforced with cotton gin waste and flax fibers. *Procedia Engineering*, 200:370–376, 2017.
- [26] Bajwa, D. S. and Bhattacharjee, S. Impact of Recycling on the Mechanical and Thermo-Mechanical Properties of Wood Fiber Based HDPE and PLA Composites. *Handbook of Composites from Renewable Materials, Physico-Chemical and Mechanical Characterization*, page 271, 2017.
- [27] Baker, R. A., Koller, L. L., and Kummer, P. E. *Calcium carbonate*. Van Nostrand Reinhold Co, New York, 1987.
- [28] Baker, R. J., White, D. J., and Leeuwen, J. V. Applications for Reuse of Lime Sludge from Water Softening. Technical report, Department of Civil, Construction and Environmental Engineering, Iowa State University, 2005.
- [29] Balaji, N. S. and Jayabal, S. Artificial neural network modeling of mechanical behaviors of zeo fiber–polyester composites. *Proceedings of the Institution of Mechanical Engineers, Part E: Journal of Process Mechanical Engineering*, 230(1):45–55, 2016.
- [30] Balasubramanian, J., Sabumon, P. C., Lazar, J. U., and Ilangovan, R. Reuse of textile effluent treatment plant sludge in building materials. *Waste management*, 26(1):22–28, 2006.
- [31] Bandopadhyay, S., Srinivasan, A., and Patil, A. G. Fly Ash-Based Polymer Matrix Composites. In *Advances in Polymer Materials and Technology*, pages 133–168. CRC Press, 2016.
- [32] Bartczak, Z., Argon, A., Cohen, R., and Weinberg, M. Toughness mechanism in semi-crystalline polymer blends: II. High-density polyethylene toughened with calcium carbonate filler particles. *Polymer*, 40(9):2347–2365, 1999.
- [33] Baruah, B. and Borah, S. Effect of lime mud on undrained shear strength of soil. In *Proceedings of the 5th Indian Young Geotechnical Engineers Conference (5IYGEC): Extended Abstracts*. Shweta Publications, 2015.
- [34] Bavan, D. S. and Kumar, G. C. M. Potential use of natural fiber composite materials in India. *Journal of Reinforced Plastics and Composites*, 29(24): 3600–3613, 2010.
- [35] Bénard, Q., Fois, M., and Grisel, M. Roughness and fibre reinforcement effect onto wettability of composite surfaces. *Applied Surface Science*, 253(10):4753–4758, 2007.
- [36] Bera, M., Alagirusamy, R., and Das, A. A study on interfacial properties of jute-PP composites. *Journal of Reinforced Plastics and Composites*, 29(20): 3155–3161, 2010.

- [37] Berghezan, A. Non-ferrous materials. *Nucleus*, 8(5):5–11, 1966.
- [38] Berthelot, J.-M. and Sefrani, Y. Damping analysis of unidirectional glass and Kevlar fibre composites. *Composites science and technology*, 64(9):1261–1278, 2004.
- [39] Betterman, L., Ouyang, C., and Shah, S. Fiber-matrix interaction in microfiber-reinforced mortar. *Advanced Cement Based Materials*, 2(2):53–61, 1995.
- [40] Bettini, S. H. P., Bicudo, A. B. L. C., Augusto, I. S., Antunes, L. A., Morassi, P. L., Condotta, R., and Bonse, B. C. Investigation on the use of coir fiber as alternative reinforcement in polypropylene. *Journal of applied polymer science*, 118(5):2841–2848, 2010.
- [41] Bhat, A. H., Khalil, H. P. S. A., Bhat, A. H., and Banthia, A. K. Dielectric and material properties of poly (vinyl alcohol): Based modified red mud polymer nanocomposites. *Journal of Polymers and the Environment*, 20(2):395–403, 2012.
- [42] Bhattacharjee, S. and Bajwa, D. S. Degradation in the mechanical and thermo-mechanical properties of natural fiber filled polymer composites due to recycling. *Construction and Building Materials*, 172:1–9, 2018.
- [43] Bijwe, J., Logani, C. M., and Tewari, U. S. Influence of fillers and fibre reinforcement on abrasive wear resistance of some polymeric composites. *Wear*, 138(1-2):77–92, 1990.
- [44] Bishay, I. K., Abd-El-Messieh, S. L., and Mansour, S. H. Electrical, mechanical and thermal properties of polyvinyl chloride composites filled with aluminum powder. *Materials & Design*, 32(1):62–68, 2011.
- [45] Biswal, M., Mohanty, S., and Nayak, S. K. Influence of organically modified nanoclay on the performance of pineapple leaf fiber-reinforced polypropylene nanocomposites. *Journal of applied polymer science*, 114(6):4091–4103, 2009.
- [46] Biswas, S. and Satapathy, A. Use of copper slag in glass-epoxy composites for improved wear resistance. *Waste Management & Research*, 28(7):615–625, 2010.
- [47] Biswas, S., Patnaik, A., and Kaundal, R. Effect of red mud and copper slag particles on physical and mechanical properties of bamboo-fiber-reinforced epoxy composites. *Advances in Mechanical Engineering*, 4:141248, 2012.
- [48] Bledzki, A., Mamun, A., Lucka-Gabor, M., and Gutowski, V. S. The effects of acetylation on properties of flax fibre and its polypropylene composites. *Express Polymer Letters*, 2(6):413–22, 2008.
- [49] Bliznakov, E. D., White, C. C., and Shaw, M. T. Mechanical properties of blends of HDPE and recycled urea-formaldehyde resin. *Journal of Applied Polymer Science*, 77(14):3220–3227, 2000.

- [50] Boontima, B., Noomhorm, A., Puttanlek, C., Uttapap, D., and Rungsardthong, V. Mechanical properties of sugarcane bagasse fiber-reinforced soy based biocomposites. *Journal of Polymers and the Environment*, 23(1):97–106, 2015.
- [51] Braem, M., Finger, W., Doren, V. E. V., Lambrechts, P., and Vanherle, G. Mechanical properties and filler fraction of dental composites. *Dental Materials*, 5(5):346–349, 1989.
- [52] Brahmakumar, M., Pavithran, C., and Pillai, R. M. Coconut fibre reinforced polyethylene composites: effect of natural waxy surface layer of the fibre on fibre/matrix interfacial bonding and strength of composites. *Composites Science and technology*, 65(3-4):563–569, 2005.
- [53] Chafidz, A., haj Ali, M. A., and Elleithy, R. Morphological, thermal, rheological, and mechanical properties of polypropylene-nanoclay composites prepared from masterbatch in a twin screw extruder. *Journal of Materials Science*, 46(18):6075–6086, 2011.
- [54] Chafidz, A., Ali, I., Mohsin, M. A., Elleithy, R., and Al-Zahrani, S. Atomic force microscopy, thermal, viscoelastic and mechanical properties of HDPE/CaCO<sub>3</sub> nanocomposites. *Journal of Polymer Research*, 19(4):1–17, 2012.
- [55] Chan, C.-M., Wu, J., Li, J.-X., and Cheung, Y.-K. Polypropylene/calcium carbonate nanocomposites. *Polymer*, 43(10):2981–2992, 2002.
- [56] Chaowasakoo, T. and Sombatsompop, N. Mechanical and morphological properties of fly ash/epoxy composites using conventional thermal and microwave curing methods. *composites science and technology*, 67(11-12):2282–2291, 2007.
- [57] Chen, J.-H., Zhong, J.-C., Cai, Y.-H., Su, W.-B., and Yang, Y.-B. Morphology and thermal properties in the binary blends of poly (propylene-co-ethylene) copolymer and isotactic polypropylene with polyethylene. *Polymer*, 48(10):2946–2957, 2007.
- [58] Cho, J., Chen, J. Y., and Daniel, I. M. Mechanical enhancement of carbon fiber/epoxy composites by graphite nanoplatelet reinforcement. *Scripta materialia*, 56(8):685–688, 2007.
- [59] Colombo, P., Brusatin, G., Bernardo, E., and Scarinci, G. Inertization and reuse of waste materials by vitrification and fabrication of glass-based products. *Current Opinion in Solid State and Materials Science*, 7(3):225–239, 2003.
- [60] Dányádi, L., Móczó, J., and Pukánszky, B. Effect of various surface modifications of wood flour on the properties of PP/wood composites. *Composites Part A: Applied Science and Manufacturing*, 41(2):199–206, 2010.

- [61] Das, O., Sarmah, A. K., and Bhattacharyya, D. A novel approach in organic waste utilization through biochar addition in wood/polypropylene composites. *Waste management*, 38:132–140, 2015.
- [62] Davies, I. J. and Sudarisman. Flexural failure of unidirectional hybrid fibre-reinforced polymer (FRP) composites containing different grades of glass fibre. In *Advanced Materials Research*, volume 41, pages 357–362. Trans Tech Publ, 2008.
- [63] Davies, I. J. and Sudarisman. Influence of compressive pressure, vacuum pressure, and holding temperature applied during autoclave curing on the microstructure of unidirectional CFRP composites. In *Advanced Materials Research*, volume 41, pages 323–328. Trans Tech Publ, 2008.
- [64] de Oliveira, L. A. P. and Castro-Gomes, J. P. Physical and mechanical behaviour of recycled PET fibre reinforced mortar. *Construction and Building Materials*, 25(4):1712–1717, 2011.
- [65] Deanin, R. D. and Chung, C. *Handbook of Polyolefins-Synthesis and Properties*, 1993.
- [66] Deepthi, M., Sharma, M., Sailaja, R., Anantha, P., Sampathkumaran, P., and Seetharamu, S. Mechanical and thermal characteristics of high density polyethylene-fly ash Cenospheres composites. *Materials & Design*, 31(4):2051–2060, 2010.
- [67] Deka, S. and Yasmin, S. Utilization of lime sludge waste from paper mills for fish culture. *Current Science*, 90(8):1126–1129, 2006.
- [68] Deshmukh, G., Pathak, S., Peshwe, D., and Ekhe, J. Effect of uncoated calcium carbonate and stearic acid coated calcium carbonate on mechanical, thermal and structural properties of poly (butylene terephthalate)(PBT)/calcium carbonate composites. *Bulletin of Materials Science*, 33(3):277–284, 2010.
- [69] Díaz, R. A. *Thermal Analysis: Fundamentals and Applications to Material Characterization: Proceedings of the International Seminar: Thermal Analysis and Rheology: Ferrol, Spain, 30 Juny-4 July 2003*. Universidade da Coruña, Servizo de Publicacións, Spain, 2005.
- [70] Dong, C. and Davies, I. J. Flexural and tensile strengths of unidirectional hybrid epoxy composites reinforced by S-2 glass and T700S carbon fibres. *Materials & Design*, 54:955–966, 2014.
- [71] Elleithy, R. H., Ali, I., Ali, M. A., and Al-Zahrani, S. High density polyethylene/micro calcium carbonate composites: A study of the morphological, thermal, and viscoelastic properties. *Journal of Applied Polymer Science*, 117(4): 2413–2421, 2010.
- [72] Erhard, G. and Thompson, M. *Designing with plastics*. Hanser Munich, Germany, 2006.

- [73] Evanylo, G. K. and Daniels, W. L. Paper mill sludge composting and compost utilization. *Compost Science & Utilization*, 7(2):30–39, 1999.
- [74] Fan, L., Dang, Z., Nan, C.-W., and Li, M. Thermal, electrical and mechanical properties of plasticized polymer electrolytes based on PEO/P (VDF-HFP) blends. *Electrochimica Acta*, 48(2):205–209, 2002.
- [75] Faruk, O., Bledzki, A. K., Fink, H.-P., and Sain, M. Progress report on natural fiber reinforced composites. *Macromolecular Materials and Engineering*, 299(1):9–26, 2014.
- [76] Finkenstadt, V. L., Liu, C.-K., Evangelista, R., Liu, L., Cermak, S. C., Hojilla-Evangelista, M., and Willett, J. L. Poly (lactic acid) green composites using oilseed coproducts as fillers. *Industrial crops and products*, 26(1):36–43, 2007.
- [77] Fombuena, V., Bernardi, L., Fenollar, O., Boronat, T., and Balart, R. Characterization of green composites from biobased epoxy matrices and bio-fillers derived from seashell wastes. *Materials & Design*, 57:168–174, 2014.
- [78] Fu, Q. and Wang, G. Polyethylene toughened by rigid inorganic particles. *Polymer Engineering & Science*, 32(2):94–97, 1992.
- [79] Fu, Q. and Wang, G. Effect of morphology on brittle-ductile transition of HPDE/CaCO<sub>3</sub> blends. *Journal of applied polymer science*, 49(11):1985–1988, 1993.
- [80] Fu, Q., Wang, G., and Shen, J. Polyethylene toughened by CaCO<sub>3</sub> particle: Brittle-ductile transition of CaCO<sub>3</sub>-toughened HDPE. *Journal of Applied Polymer Science*, 49(4):673–677, 1993.
- [81] Fu, S.-Y., Feng, X.-Q., Lauke, B., and Mai, Y.-W. Effects of particle size, particle/matrix interface adhesion and particle loading on mechanical properties of particulate–polymer composites. *Composites Part B: Engineering*, 39(6):933–961, 2008.
- [82] Gangil, B., Patnaik, A., Kumar, A., and Biswas, S. Thermo-mechanical and sliding wear behaviour of vinyl ester–cement by-pass dust particulate-filled homogenous and their functionally graded composites. *Proceedings of the Institution of Mechanical Engineers, Part J: Journal of Engineering Tribology*, 227(3):246–258, 2013.
- [83] Garoushi, S., Vallittu, P. K., and Lassila, L. V. J. Short glass fiber reinforced restorative composite resin with semi-inter penetrating polymer network matrix. *Dental materials*, 23(11):1356–1362, 2007.
- [84] Geethamma, V. G., Mathew, K. T., Lakshminarayanan, R., and Thomas, S. Composite of short coir fibres and natural rubber: effect of chemical modification, loading and orientation of fibre. *Polymer*, 39(6-7):1483–1491, 1998.
- [85] Girones, J., Pardini, G., Vilaseca, F., Pelach, M. A., and Mutje, P. Recycling of paper mill sludge as filler/reinforcement in polypropylene composites. *Journal of Polymers and the Environment*, 18(3):407–412, 2010.

- [86] Gracia, R., Evans, R. E., Palmer, R. J., and Johnson, N. J. Toughened composites. *STP*, 937:397–412, 1987.
- [87] Gu, J., Wu, G., and Zhang, Q. Effect of porosity on the damping properties of modified epoxy composites filled with fly ash. *Scripta materialia*, 57(6): 529–532, 2007.
- [88] Gulmine, J., Janissek, P., Heise, H., and Akcelrud, L. Polyethylene characterization by FTIR. *Polymer Testing*, 21(5):557–563, 2002.
- [89] Gupta, A., Singh, H., and Walia, R. Effect of fillers on tensile strength of pultruded glass fiber reinforced polymer composite. *Indian Journal of Engineering and Materials Sciences*, 22(1):62–70, 2015.
- [90] Gupta, A. P., Saroop, U. K., and Verma, M. Studies of mechanical and thermal properties of polypropylene/LLDPE-copolymer blends and its glass fiber compositions. *Polymer-Plastics Technology and Engineering*, 43(3):937–950, 2004.
- [91] Gupta, G. and Satapathy, A. Processing, characterization, and erosion wear characteristics of borosilicate glass microspheres filled epoxy composites. *Polymer Composites*, 36(9):1685–1692, 2015.
- [92] Guth, E. Theory of filler reinforcement. *Journal of applied physics*, 16(1): 20–25, 1945.
- [93] Guth, E. and Gold, O. On the hydrodynamical theory of the viscosity of suspensions. *Physical Review*, 53(322):2–15, 1938.
- [94] Guzel, G. and Deveci, H. Physico-mechanical, thermal, and coating properties of composite materials prepared with epoxy resin/steel slag. *Polymer Composites*, 38(9):1974–1981, 2017.
- [95] Guzel, G. and Deveci, H. Properties of polymer composites based on bisphenol A epoxy resins with original/modified steel slag. *Polymer Composites*, 39(2): 513–521, 2018.
- [96] Haque, M. M., Hasan, M., Islam, M. S., and Ali, M. E. Physico-mechanical properties of chemically treated palm and coir fiber reinforced polypropylene composites. *Bioresource Technology*, 100(20):4903–4906, 2009.
- [97] Haque, R., Saxena, M., Shit, S. C., and Asokan, P. Fibre-matrix adhesion and properties evaluation of sisal polymer composite. *Fibers and Polymers*, 16(1): 146–152, 2015.
- [98] Harish, S., Michael, D. P., Bensely, A., Lal, D. M., and Rajadurai, A. Mechanical property evaluation of natural fiber coir composite. *Materials characterization*, 60(1):44–49, 2009.



- [99] Hartikainen, J., Hine, P., Szabo, J. S., Lindner, M., Harmia, T., Duckett, R. A., and Friedrich, K. Polypropylene hybrid composites reinforced with long glass fibres and particulate filler. *Composites Science and Technology*, 65(2):257–267, 2005.
- [100] Hassan, S. B., Oghenevweta, J. E., and Aigbodion, V. S. Morphological and mechanical properties of carbonized waste maize stalk as reinforcement for eco-composites. *Composites Part B: Engineering*, 43(5):2230–2236, 2012.
- [101] Herrera-Franco, P., Valadez-Gonzalez, A., and Cervantes-Uc, M. Development and characterization of a HDPE-sand-natural fiber composite. *Composites Part B: Engineering*, 28(3):331–343, 1997.
- [102] Hill, C. A. S., Khalil, H. P. S. A., and Hale, M. D. A study of the potential of acetylation to improve the properties of plant fibres. *Industrial Crops and Products*, 8(1):53–63, 1998.
- [103] Huang, H. B., Du, H. H., Wang, W. H., and Shi, J. Y. Characteristics of paper mill sludge-wood fiber-high-density polyethylene composites. *Polymer Composites*, 33(9):1628–1634, 2012.
- [104] il Kim, J., Kang, P. H., and Nho, Y. C. Positive temperature coefficient behavior of polymer composites having a high melting temperature. *Journal of Applied Polymer Science*, 92(1):394–401, 2004.
- [105] Jana, S. C. and Jain, S. Dispersion of nanofillers in high performance polymers using reactive solvents as processing aids. *Polymer*, 42(16):6897–6905, 2001.
- [106] Jang, B. Z. Advanced polymer composites: principles and applications. *ASM International, Materials Park, OH 44073-0002, USA, 1994. 305*, 1994.
- [107] Jartiz, A. E. *Design*. 1965.
- [108] Jayabal, S. and Natarajan, U. Regression & neuro fuzzy models for prediction of thrust force and torque in drilling of glass fibre reinforced composites. *The International Journal of Advanced Manufacturing Technology*, 69(10):741–745, 2010.
- [109] Jayabal, S. and Natarajan, U. Optimization of thrust force, torque, and tool wear in drilling of coir fiber-reinforced composites using nelder–mead and genetic algorithm methods. *The International Journal of Advanced Manufacturing Technology*, 51(1-4):371–381, 2010.
- [110] Jayabal, S. and Natarajan, U. Influence of fiber parameters on tensile, flexural, and impact properties of nonwoven coir–polyester composites. *The International Journal of Advanced Manufacturing Technology*, 54(5-8):639–648, 2011.
- [111] Jayabal, S., Sathiyamurthy, S., Loganathan, K. T., and Kalyanasundaram, S. Effect of soaking time and concentration of NaOH solution on mechanical properties of coir–polyester composites. *Bulletin of Materials Science*, 35(4): 567–574, 2012.

- [112] Jayabal, S., Rajamuneeswaran, S., Ramprasath, R., and Balaji, N. S. Artificial neural network modeling of mechanical properties of calcium carbonate impregnated coir-polyester composites. *Transactions of the Indian Institute of Metals*, 66(3):247–255, 2013.
- [113] Jerabek, M., Major, Z., Renner, K., Móczó, J., Pukánszky, B., and Lang, R. W. Filler/matrix-debonding and micro-mechanisms of deformation in particulate filled polypropylene composites under tension. *Polymer*, 51(9):2040–2048, 2010.
- [114] Jose, S., Aprem, A. S., Francis, B., Chandy, M. C., Werner, P., Alstaedt, V., and Thomas, S. Phase morphology, crystallisation behaviour and mechanical properties of isotactic polypropylene/high density polyethylene blends. *European polymer journal*, 40(9):2105–2115, 2004.
- [115] Joshi, S. V., Drzal, L. T., Mohanty, A. K., and Arora, S. Are natural fiber composites environmentally superior to glass fiber reinforced composites? *Composites Part A: Applied science and manufacturing*, 35(3):371–376, 2004.
- [116] Kamble, A., Singh, V., Thomas, M., and John, N. Effectiveness of compatibilizers and filler on the performance of the blends of thermoplastic polyurethane/polyolefins. *Chemical Sciences Journal*, 34:1–9, 2011.
- [117] Kang, J. T., Park, S. H., and Kim, S. H. Improvement in the adhesion of bamboo fiber reinforced polylactide composites. *Journal of Composite Materials*, 48(21):2567–2577, 2014.
- [118] Karsli, N. G. and Aytac, A. Tensile and thermomechanical properties of short carbon fiber reinforced polyamide 6 composites. *Composites Part B: Engineering*, 51:270–275, 2013.
- [119] Kato, T. Polymer/calcium carbonate layered thin-film composites. *Advanced Materials*, 12(20):1543–1546, 2000.
- [120] Kaw, A. K. *Mechanics of composite materials*. CRC press, 2005.
- [121] Kaya, G. G., Yilmaz, E., and Deveci, H. Sustainable bean pod/calcined kaolin reinforced epoxy hybrid composites with enhanced mechanical, water sorption and corrosion resistance properties. *Construction and Building Materials*, 162: 272–279, 2018.
- [122] Kazayawoko, M. and Balatinecz, J. J. Adhesion mechanisms in woodfiber-polypropylene composites. In *Fourth international conference on woodfiber-plastic composites*. Madison: Forest Products Research Soc, pages 81–93, 1997.
- [123] Kelly, A. The nature of composite materials. *Scientific American*, 217(3): 160–179, 1967.
- [124] Khademieslam, H. and Kalagar, M. Evaluation of the Bending Strength, Impact Strength, and Morphological Properties of Wheat Straw Fiber/Paper Mill Sludge/Polypropylene Composites. *BioResources*, 11(2):3914–3922, 2016.

- [125] Khalil, H. P. S. A., Ismail, H., Rozman, H. D., and Ahmad, M. N. The effect of acetylation on interfacial shear strength between plant fibres and various matrices. *European Polymer Journal*, 37(5):1037–1045, 2001.
- [126] Khalil, H. P. S. A., Tehrani, M. A., Davoudpour, Y., Bhat, A. H., Jawaid, M., and Hassan, A. Natural fiber reinforced poly (vinyl chloride) composites: A review. *Journal of Reinforced Plastics and Composites*, 32(5):330–356, 2013.
- [127] Kim, H., Biswas, J., and Choe, S. Effects of stearic acid coating on zeolite in LDPE, LLDPE, and HDPE composites. *Polymer*, 47(11):3981–3992, 2006.
- [128] Kim, H.-S., Lee, B.-H., Choi, S.-W., Kim, S., and Kim, H.-J. The effect of types of maleic anhydride-grafted polypropylene (MAPP) on the interfacial adhesion properties of bio-flour-filled polypropylene composites. *Composites Part A: Applied Science and Manufacturing*, 38(6):1473–1482, 2007.
- [129] Kim, K.-J., White, J. L., Shim, S. E., and Choe, S. Effects of stearic acid coated talc,  $\text{CaCO}_3$ , and mixed talc/ $\text{CaCO}_3$  particles on the rheological properties of polypropylene compounds. *Journal of Applied Polymer Science*, 93(5):2105–2113, 2004.
- [130] Kim, Y. D., Oh, N. L., Oh, S.-T., and Moon, I.-H. Thermal conductivity of W–Cu composites at various temperatures. *Materials Letters*, 51(5):420–424, 2001.
- [131] Knight, G. W. Polyethylene. In *Polymer Toughening*, pages 189–235. Marcel Dekker Inc, Monticello, NY 12701-5185, USA, 1996.
- [132] Koshikawa, M. and Isogai, A. Analyses of incinerated ash of paper sludge: comparison with incinerated ash of municipal solid waste. *Journal of Material Cycles and Waste Management*, 6(1):64–72, 2004.
- [133] Kovacevic, V., Lucic, S., Hace, D., and Glasnovic, A. Rheology and morphology of poly (vinyl acetate)+ calcite films. *Polymer Engineering & Science*, 36(8):1134–1139, 1996.
- [134] Kumar, R. S. and Rajkumar, P. Characterization of minerals in air dust particles in the state of Tamilnadu, India through FTIR, XRD and SEM analyses. *Infrared Physics & Technology*, 67:30–41, 2014.
- [135] Kumar, S., Reddy, K. V. V. S. M., Kumar, A., and Devi, G. R. Development and characterization of polymer–ceramic continuous fiber reinforced functionally graded composites for aerospace application. *Aerospace Science and Technology*, 26(1):185–191, 2013.
- [136] Kwon, S., Kim, K. J., Kim, H., Kundu, P. P., Kim, T. J., Lee, Y. K., Lee, B. H., and Choe, S. Tensile property and interfacial dewetting in the calcite filled HDPE, LDPE, and LLDPE composites. *Polymer*, 43(25):6901–6909, 2002.

- [137] Landel, R. F. and Nielsen, L. E. *Mechanical properties of polymers and composites*. CRC press, 1993.
- [138] Lauke, B. and Fu, S.-Y. Aspects of fracture toughness modelling of particle filled polymer composites. *Composites Part B: Engineering*, 45(1):1569–1574, 2013.
- [139] Laul, A. Interview on sustainable architectural practice. *Down to Earth*, 11(2):43, 2002.
- [140] Lei, Y., Wu, Q., Yao, F., and Xu, Y. Preparation and properties of recycled HDPE/natural fiber composites. *Composites Part A: Applied Science and Manufacturing*, 38(7):1664–1674, 2007.
- [141] Leong, Y., Bakar, A., Ishak, Z., Ariffin, A., and Pukanszky, B. Comparison of the mechanical properties and interfacial interactions between talc, kaolin, and calcium carbonate filled polypropylene composites. *Journal of Applied Polymer Science*, 91(5):3315–3326, 2004.
- [142] Leprince, J., Palin, W. M., Mullier, T., Devaux, J., Vreven, J., and Leloup, G. Investigating filler morphology and mechanical properties of new low-shrinkage resin composite types. *Journal of Oral Rehabilitation*, 37(5):364–376, 2010.
- [143] Li, K., Qiu, R., and Liu, W. Improvement of interfacial adhesion in natural plant fiber-reinforced unsaturated polyester composites: A critical review. *Reviews of Adhesion and Adhesives*, 3(1):98–120, 2015.
- [144] Li, L., Zou, H., Shao, L., Wang, G., and Chen, J. Study on mechanical property of epoxy composite filled with nano-sized calcium carbonate particles. *Journal of materials science*, 40(5):1297–1299, 2005.
- [145] Li, X., Tabil, L. G., and Panigrahi, S. Chemical treatments of natural fiber for use in natural fiber-reinforced composites: a review. *Journal of Polymers and the Environment*, 15(1):25–33, 2007.
- [146] Li, Z., Wang, X., and Wang, L. Properties of hemp fibre reinforced concrete composites. *Composites Part A: Applied science and manufacturing*, 37(3):497–505, 2006.
- [147] Liao, J. Y., Jang, B. Z., Hwang, L. R., and Wilcox, R. C. Toughening composites by matrix modification. *Plastics Engineering*, 44(11):33, 1988.
- [148] Lin, Y., Chen, H., Chan, C.-M., and Wu, J. High impact toughness polypropylene/CaCO<sub>3</sub> nanocomposites and the toughening mechanism. *Macromolecules*, 41(23):9204–9213, 2008.
- [149] Liu, L., Zhang, Y., Lv, F., Yang, B., and Meng, X. Effects of red mud on rheological, crystalline, and mechanical properties of red mud/PBAT composites. *Polymer Composites*, 37(7):2001–2007, 2016.
- [150] Liu, Z., Maréchal, P., and Jérôme, R. DMA and DSC investigations of the  $\beta$  transition of poly (vinylidene fluoride). *Polymer*, 38(19):4925–4929, 1997.

- [151] Ma, F., Chen, S., Liu, P., Geng, F., Li, W., Liu, X., He, D., and Pan, D. Improvement of  $\beta$ -TCP/PLLA biodegradable material by surface modification with stearic acid. *Materials Science and Engineering: C*, 62:407–413, 2016.
- [152] Mahapatra, S. S. Modelling and analysis of erosion wear behaviour of hybrid composites using Taguchi experimental design. *Proceedings of the Institution of Mechanical Engineers, Part J: Journal of Engineering Tribology*, 224(2): 157–167, 2010.
- [153] Mahata, T., Prakash, D., Sharma, B. P., and Nair, S. R. Formation of aluminum titanate-mullite composite from bauxite red mud. *Metallurgical and Materials Transactions B*, 31(3):551–553, 2000.
- [154] Majeed, K., Hassan, A., and Bakar, A. A. Barrier, Biodegradation, and mechanical properties of (Rice husk)/(Montmorillonite) hybrid filler-filled low-density polyethylene nanocomposite films. *Journal of Vinyl and Additive Technology*, 23(3):162–171, 2017.
- [155] Malkapuram, R., Kumar, V., and Negi, Y. S. Recent development in natural fiber reinforced polypropylene composites. *Journal of Reinforced Plastics and Composites*, 28(10):1169–1189, 2009.
- [156] Mallick, P. K. *Fiber-reinforced composites: materials, manufacturing, and design*. CRC press, 2007.
- [157] Manders, P. W. and Bader, M. G. The strength of hybrid glass/carbon fibre composites. *Journal of Materials Science*, 16(8):2233–2245, 1981.
- [158] Mareri, P., Bastide, S., Binda, N., and Crespy, A. Mechanical behaviour of polypropylene composites containing fine mineral filler: Effect of filler surface treatment. *Composites Science and Technology*, 58(5):747–752, 1998.
- [159] Martí-Ferrer, F., Vilaplana, F., Ribes-Greus, A., Benedito-Borrás, A., and Sanz-Box, C. Flour rice husk as filler in block copolymer polypropylene: Effect of different coupling agents. *Journal of Applied Polymer Science*, 99(4):1823–1831, 2006.
- [160] Matějka, V., Fu, Z., Kukutschová, J., Qi, S., Jiang, S., Zhang, X., Yun, R., Vaculík, M., Heliová, M., and Lu, Y. Jute fibers and powderized hazelnut shells as natural fillers in non-asbestos organic non-metallic friction composites. *Materials & Design*, 51:847–853, 2013.
- [161] Mir, S. S., Nafsin, N., Hasan, M., Hasan, N., and Hassan, A. Improvement of physico-mechanical properties of coir-polypropylene biocomposites by fiber chemical treatment. *Materials & Design*, 52:251–257, 2013.
- [162] Misra, R., Nerikar, P., Bertrand, K., and Murphy, D. Some aspects of surface deformation and fracture of 5–20% calcium carbonate-reinforced polyethylene composites. *Materials Science and Engineering: A*, 384(1):284–298, 2004.

- [163] Mohanty, S., Verma, S. K., and Nayak, S. K. Dynamic mechanical and thermal properties of MAPE treated jute/HDPE composites. *Composites Science and Technology*, 66(3-4):538–547, 2006.
- [164] Mohsenzadeh, M., Zebarjad, S. M., and Mazinani, M. Deformation mechanics of polyethylene/calcium carbonate nanocomposites. In *18th International Conference on Composite Materials*, 2011.
- [165] Morandim-Giannetti, A. A., Agnelli, J. A. M., Lanças, B. Z., Magnabosco, R., Casarin, S. A., and Bettini, S. H. P. Lignin as additive in polypropylene/coir composites: Thermal, mechanical and morphological properties. *Carbohydrate Polymers*, 87(4):2563–2568, 2012.
- [166] Mulinari, D. R., Baptista, C. A. R. P., Souza, J. V. C., and Voorwald, H. J. C. Mechanical properties of coconut fibers reinforced polyester composites. *Procedia Engineering*, 10:2074–2079, 2011.
- [167] Muthu, J., Priscilla, J., Odeshi, A., and Kuppen, N. Characterisation of coir fibre hybrid composites reinforced with clay particles and glass spheres. *Journal of Composite Materials*, 0:1–15, 2017. doi: 10.1177/0021998317712568.
- [168] Nakamura, Y., Yamaguchi, M., Kitayama, A., Okubo, M., and Matsumoto, T. Effect of particle size on fracture toughness of epoxy resin filled with angular-shaped silica. *Polymer*, 32(12):2221–2229, 1991.
- [169] Nakamura, Y., Yamaguchi, M., Okubo, M., and Matsumoto, T. Effects of particle size on mechanical and impact properties of epoxy resin filled with spherical silica. *Journal of applied polymer science*, 45(7):1281–1289, 1992.
- [170] Nam, T. H., Ogihara, S., Tung, N. H., and Kobayashi, S. Effect of alkali treatment on interfacial and mechanical properties of coir fiber reinforced poly (butylene succinate) biodegradable composites. *Composites Part B: Engineering*, 42(6):1648–1656, 2011.
- [171] Naozuka, J., Vieira, E. C., Nascimento, A. N., and Oliveira, P. V. Elemental analysis of nuts and seeds by axially viewed ICP OES. *Food Chemistry*, 124(4):1667–1672, 2011.
- [172] Nayak, S. K., Mohanty, S., and Samal, S. K. Influence of interfacial adhesion on the structural and mechanical behavior of PP-banana/glass hybrid composites. *Polymer Composites*, 31(7):1247–1257, 2010.
- [173] Nedkov, T. and Lednický, F. Morphologies of polyethylene-ethylene/propylene/diene monomer particles in polypropylene-rich polyolefin blends: Flake structure. *Journal of applied polymer science*, 90(11):3087–3092, 2003.
- [174] Nikkeshi, S., Kudo, M., and Masuko, T. Dynamic viscoelastic properties and thermal properties of Ni powder-epoxy resin composites. *Journal of Applied Polymer Science*, 69(13):2593–2598, 1998.

- [175] Nitta, K.-H., Shin, Y.-W., Hashiguchi, H., Tanimoto, S., and Terano, M. Morphology and mechanical properties in the binary blends of isotactic polypropylene and novel propylene-co-olefin random copolymers with isotactic propylene sequence 1. Ethylene-propylene copolymers. *Polymer*, 46(3):965–975, 2005.
- [176] Ogunsile, B. O. and Palsule, S. Influence of amount of MAPE compatibiliser on tensile properties of hardwood fiber reinforced high density polyethylene composite. *Applied Polymer Composites*, 1(4):225–229, 2013.
- [177] Omar, M. F., Akil, H. M., and Ahmad, Z. A. Particle size-Dependent on the static and dynamic compression properties of polypropylene/silica composites. *Materials & Design*, 45:539–547, 2013.
- [178] Orue, A., Jauregi, A., Unsuain, U., Labidi, J., Eceiza, A., and Arbelaz, A. The effect of alkaline and silane treatments on mechanical properties and breakage of sisal fibers and poly (lactic acid)/sisal fiber composites. *Composites Part A: Applied Science and Manufacturing*, 84:186–195, 2016.
- [179] Osman, M. A., Atallah, A., and Suter, U. W. Influence of excessive filler coating on the tensile properties of LDPE-calcium carbonate composites. *Polymer*, 45(4):1177–1183, 2004.
- [180] Ota, W. N., Amico, S. C., and Satyanarayana, K. G. Studies on the combined effect of injection temperature and fiber content on the properties of polypropylene-glass fiber composites. *Composites science and technology*, 65(6):873–881, 2005.
- [181] Padhi, P. K. and Satapathy, A. Processing and wear analysis of blast furnace slag filled polypropylene composites using Taguchi model and ANN. *International Polymer Processing*, 29(2):233–244, 2014.
- [182] Pan, G., Zhao, Y., Xu, H., Hou, X., and Yang, Y. Compression molded composites from discarded nylon 6/nylon 6, 6 carpets for sustainable industries. *Journal of Cleaner Production*, 117:212–220, 2016.
- [183] Pandey, P., Bajwa, S., and Bajwa, D. Fiber from DDGS and Corn Grain as Alternative Fillers in Polymer Composites with High Density Polyethylene from Bio-based and Petroleum Sources. *Journal of Polymers and the Environment*, 26(6):2311–2322, 2018.
- [184] Pardo, S. G., Bernal, C., Ares, A., Abad, M. J., and Cano, J. Rheological, thermal, and mechanical characterization of fly ash-thermoplastic composites with different coupling agents. *Polymer Composites*, 31(10):1722–1730, 2010.
- [185] Park, J., Yu, M. K., Jeong, Y. Y., Kim, J. W., Lee, K., Phan, V. N., and Jon, S. Antibiofouling amphiphilic polymer-coated superparamagnetic iron oxide nanoparticles: synthesis, characterization, and use in cancer imaging in vivo. *Journal of Materials Chemistry*, 19(35):6412–6417, 2009.

- [186] Patil, A. G., Poornachandra, S., Gumageri, R., Rajkumar, K., and Anandhan, S. Chitosan composites reinforced with nanostructured waste fly ash. *Journal of Material Cycles and Waste Management*, 19(2):870–883, 2017.
- [187] Patnaik, A., Satapathy, A., Mahapatra, S. S., and Dash, R. R. A comparative study on different ceramic fillers affecting mechanical properties of glasspolyester composites. *Journal of Reinforced Plastics and Composites*, 28(11):1305–1318, 2009.
- [188] Patnaik, A., Satapathy, A., Dwivedy, M., and Biswas, S. Wear behavior of plant fiber (pine-bark) and cement kiln dust-reinforced polyester composites using Taguchi experimental model. *Journal of composite materials*, 44(5):559–574, 2010.
- [189] Peters, S. T. *Handbook of composites*. Springer Science & Business Media, 2013.
- [190] Prasad, S. V., Pavithran, C., and Rohatgi, P. K. Alkali treatment of coir fibres for coir-polyester composites. *Journal of materials science*, 18(5):1443–1454, 1983.
- [191] Praveen, S., Chattopadhyay, P. K., Albert, P., Dalvi, V. G., Chakraborty, B. C., and Chattopadhyay, S. Synergistic effect of carbon black and nanoclay fillers in styrene butadiene rubber matrix: development of dual structure. *Composites Part A: Applied Science and Manufacturing*, 40(3):309–316, 2009.
- [192] Premphet, K. and Horanont, P. Influence of stearic acid treatment of filler particles on the structure and properties of ternary-phase polypropylene composites. *Journal of applied polymer science*, 74(14):3445–3454, 1999.
- [193] Pujari, S., Ramakrishna, A., and Padal, K. T. B. Comparison of ANN and Regression Analysis for Predicting the Water Absorption Behaviour of Jute and Banana Fiber Reinforced Epoxy composites. *Materials Today: Proceedings*, 4(2):1626–1633, 2017.
- [194] Pukanszky, B. Particulate filled polypropylene: structure and properties. In *Polypropylene structure, blends and composites*, pages 1–70. Springer, 1995.
- [195] Pukanszky, B. and Vörös, G. Mechanism of interfacial interactions in particulate filled composites. *Composite Interfaces*, 1(5):411–427, 1993.
- [196] Rachchh, N. V., Misra, R. K., and Roychowdhary, D. G. Effect of red mud filler on mechanical and buckling characteristics of coir fibre-reinforced polymer composite. *Iranian Polymer Journal*, 24(3):253–265, 2015.
- [197] Rachini, A., Troedec, M. L., Peyratout, C., and Smith, A. Chemical modification of hemp fibers by silane coupling agents. *Journal of Applied Polymer Science*, 123(1):601–610, 2012.
- [198] Radford, K. C. The mechanical properties of an epoxy resin with a second phase dispersion. *Journal of Materials Science*, 6(10):1286–1291, 1971.



- [199] Rahmani, M., Ghasemi, F. A., and Payganeh, G. Effect of surface modification of calcium carbonate nanoparticles on their dispersion in the polypropylene matrix using stearic acid. *Mechanics & Industry*, 15(1):63–67, 2014.
- [200] Raja, R. S., Manisekar, K., and Manikandan, V. Study on mechanical properties of fly ash impregnated glass fiber reinforced polymer composites using mixture design analysis. *Materials & Design*, 55:499–508, 2014.
- [201] Rajamuneeswaran, S. and Jayabal, S. A lexicographic multiobjective genetic algorithm for optimization of mechanical properties of crab carapace impregnated coir–polyester composites. *Polymer Composites*, 37(3):844–853, 2016.
- [202] Rajmohan, T., Koundinya, U. K., Premnath, A. A., and Harish, G. Evaluation of mechanical properties of nano filled glass fiber reinforced composites. In *Advanced Nanomaterials and Emerging Engineering Technologies (ICAN-MEET), 2013 International Conference on*, pages 112–115. IEEE, 2013.
- [203] Ramesh, M., Palanikumar, K., and Reddy, K. H. Influence of fiber orientation and fiber content on properties of sisal-jute-glass fiber-reinforced polyester composites. *Journal of Applied Polymer Science*, 133(6), 2016.
- [204] Ramprasath, R. and Jayabal, S. Particle swarm and simulated annealing based intuitive search optimization of flexural behaviors in bioparticles impregnated coir fiber–vinyl ester composites. *Polymer Composites*, 37(6):1765–1774, 2016.
- [205] Rana, A. K., Mandal, A., Mitra, B. C., Jacobson, R., Rowell, R., and Banerjee, A. N. Short jute fiber-reinforced polypropylene composites: Effect of compatibilizer. *Journal of Applied Polymer Science*, 69(2):329–338, 1998.
- [206] Ranganath, S. A review on particulate-reinforced titanium matrix composites. *Journal of Materials Science*, 32(1):1–16, 1997.
- [207] Rigolo, M. and Woodhams, R. T. Basic magnesium carbonate flame retardants for polypropylene. *Polymer Engineering & Science*, 32(5):327–334, 1992.
- [208] Riley, A., Paynter, C., McGenity, P., and Adams, J. Factors affecting the impact properties of mineral filled polypropylene. *Plastics and rubber processing and applications*, 14(2):85–93, 1990.
- [209] Rohatgi, P., Satyanarayana, K., and Chand, N. International encyclopedia on composites, vol. 4. *VCH, New York*, 4:9, 1991.
- [210] Rong, M. Z., Zhang, M. Q., Zheng, Y. X., Zeng, H. M., Walter, R., and Friedrich, K. Structure–property relationships of irradiation grafted nano-inorganic particle filled polypropylene composites. *Polymer*, 42(1):167–183, 2001.
- [211] Rosa, S. M. L., Santos, E. F., Ferreira, C. A., and Nachtigall, S. M. B. Studies on the properties of rice-husk-filled-PP composites: effect of maleated PP. *Materials Research*, 12(3):333–338, 2009.

- [212] Rout, J., Misra, M., Tripathy, S. S., Nayak, S. K., and Mohanty, A. K. The influence of fibre treatment on the performance of coir-polyester composites. *Composites Science and Technology*, 61(9):1303–1310, 2001.
- [213] Rout, J., Misra, M., Mohanty, A. K., Nayak, S. K., and Tripathy, S. S. SEM observations of the fractured surfaces of coir composites. *Journal of reinforced plastics and composites*, 22(12):1083–1100, 2003.
- [214] Rozman, H. D., Tay, G. S., Kumar, R. N., Abubakar, A., Ismail, H., and Ishak, Z. A. M. Polypropylene hybrid composites: a preliminary study on the use of glass and coconut fiber as reinforcements in polypropylene composites. *Polymer-Plastics Technology and Engineering*, 38(5):997–1011, 1999.
- [215] Rungruang, P., Grady, B. P., and Supaphol, P. Surface-modified calcium carbonate particles by admicellar polymerization to be used as filler for isotactic polypropylene. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*, 275(1):114–125, 2006.
- [216] Saba, N., Jawaid, M., Allothman, O. Y., Inuwa, I. M., and Hassan, A. A review on potential development of flame retardant kenaf fibers reinforced polymer composites. *Polymers for Advanced Technologies*, 28(4):424–434, 2017.
- [217] Safwan, A., Jawaid, M., Sultan, M. T. H., and Hassan, A. Preliminary Study on Tensile and Impact Properties of Kenaf/Bamboo Fiber Reinforced Epoxy Composites. *Journal of Renewable Materials*, 2018.
- [218] Sahebian, S., Zebarjad, S. M., Khaki, J. V., and Sajjadi, S. A. The effect of nano-sized calcium carbonate on thermodynamic parameters of HDPE. *Journal of Materials Processing Technology*, 209(3):1310–1317, 2009.
- [219] Saidi, M. A. A., Ahmad, M., Arjmandi, R., Hassan, A., and Rahmat, A. R. The Effect of Titanate Coupling Agent on Water Absorption and Mechanical Properties of Rice Husk Filled Poly (vinyl Chloride) Composites. In *Natural Fibre Reinforced Vinyl Ester and Vinyl Polymer Composites*, pages 197–210. Elsevier, 2018.
- [220] Saini, A., Yadav, C., Bera, M., Gupta, P., and Maji, P. K. Maleic anhydride grafted linear low-density polyethylene/waste paper powder composites with superior mechanical behavior. *Journal of Applied Polymer Science*, 134(31), 2017.
- [221] Salmah, H., Ruzaidi, C. M., and Supri, A. G. Compatibilisation of polypropylene/ethylene propylene diene terpolymer/kaolin composites: the effect of maleic anhydride-grafted-polypropylene. *Journal of Physical Science*, 20(1): 99–107, 2009.
- [222] Samat, N., Sabaruddin, F. A., Yusoff, M. M., and Habibah, A. D. Evaluation of Waste from Aluminum Industry as Filler in Polypropylene Composites. *JOM*, 69(4):790–795, 2017.

- [223] Saradava, B. J., Rachchh, N. V., Misra, R. K., and Roychowdhary, D. G. Mechanical characterization of coir fiber reinforced polymer composite using red mud as filler. *Journal of Information, Knowledge and Research in Mechanical Engineering*, 2(2):472–476, 2013.
- [224] Sarkar, A. and Mahapatra, S. Novel hydrophobic vaterite particles for oil removal and recovery. *Journal of Materials Chemistry A*, 2(11):3808–3818, 2014.
- [225] Sarker, M., Rashid, M. M., and Molla, M. Abundant high-density polyethylene (HDPE-2) turns into fuel by using of HZSM-5 catalyst. *The Journal of Fundamentals of Renewable Energy and Applications*, 1:1–12, 2011.
- [226] Sarker, M., Rashid, M. M., Rahman, M. S., and Molla, M. Chemical Products Produced from High Density Polyethylene (HDPE) Waste Plastic. *International Journal of Material Science*, 2(3):56–62, 2012.
- [227] Satapathy, S. and Kothapalli, R. V. S. Mechanical, dynamic mechanical and thermal properties of banana fiber/recycled high density polyethylene biocomposites filled with flyash cenospheres. *Journal of Polymers and the Environment*, pages 1–14, 2017.
- [228] Satapathy, S., Nando, G. B., Jose, J., and Nag, A. Mechanical properties and fracture behavior of short pet fiber-waste polyethylene composites. *Journal of Reinforced Plastics and Composites*, 27(9):967–984, 2008.
- [229] Satapathy, S., Nag, A., and Nando, G. B. Effect of electron beam irradiation on the mechanical, thermal, and dynamic mechanical properties of flyash and nanostructured fly ash waste polyethylene hybrid composites. *Polymer Composites*, 33(1):109–119, 2012.
- [230] Satapathy, S., Nando, G. B., Nag, A., and Raju, K. V. S. N. HDPE-fly ash/nano fly ash Composites. *Journal of Applied Polymer Science*, 130(6):4558–4567, 2013.
- [231] Sathiyamurthy, S., Thaheer, A., and Jayabal, S. Prediction and optimization of mechanical properties of particles filled coir-polyester composites using ANN and RSM algorithms. *Indian Journal of Fibre & Textile Research*, 38(1):81–86, 2013.
- [232] Sathiyamurthy, S., Thaheer, A., and Jayabal, S. Modelling and optimization of mechanical behaviors of Al<sub>2</sub>O<sub>3</sub>-coir-polyester composites using response surface methodology. *Indian Journal of Fibre & Textile Research*, 38(1):81–86, 2013.
- [233] Sato, Y. and Furukawa, J. A molecular theory of filler reinforcement based on the concept of internal deformation. *Rubber Chemistry and Technology*, 35(4):857–876, 1962.

- [234] Satyanarayana, K. G., Sukumaran, K., Kulkarni, A. G., Pillai, S. G. K., and Rohatgi, P. K. Fabrication and properties of natural fibre-reinforced polyester composites. *Composites*, 17(4):329–333, 1986.
- [235] Satyanarayana, K. G., Guimarães, J. L., and Wypych, F. Studies on lignocellulosic fibers of Brazil. Part I: Source, production, morphology, properties and applications. *Composites Part A: Applied Science and Manufacturing*, 38(7):1694–1709, 2007.
- [236] Sawyer, W. G., Freudenberg, K. D., Bhimaraj, P., and Schadler, L. S. A study on the friction and wear behavior of PTFE filled with alumina nanoparticles. *Wear*, 254(5-6):573–580, 2003.
- [237] Siddhartha, V., Patnaik, A., and Bhatt, A. D. Friction and wear analysis of a cement kiln dust-reinforced epoxy-based functionally graded materials. *Proceedings of the Institution of Mechanical Engineers, Part J: Journal of Engineering Tribology*, 224(10):1103–1114, 2010.
- [238] Singh, A. A. and Palsule, S. Coconut fiber reinforced chemically functionalized high-density polyethylene (CNF/CF-HDPE) composites by Palsule process. *Journal of Composite Materials*, 48(29):3673–3684, 2014.
- [239] Singh, A. A. and Palsule, S. Jute fiber reinforced chemically functionalized polypropylene self-compatibilizing composites by Palsule process. *Journal of Composite Materials*, 50(9):1199–1212, 2016.
- [240] Singh, M. and Garg, M. Utilization of waste lime sludge as building materials. *Journal of Scientific and Industrial Research*, 67(2):161–166, 2008.
- [241] Sinha, E. and Panigrahi, S. Effect of plasma treatment on structure, wettability of jute fiber and flexural strength of its composite. *Journal of Composite Materials*, 43(17):1791–1802, 2009.
- [242] Sommerhuber, P. F., Welling, J., and Krause, A. Substitution potentials of recycled HDPE and wood particles from post-consumer packaging waste in Wood–Plastic Composites. *Waste management*, 46:76–85, 2015.
- [243] Sommerhuber, P. F., Wang, T., and Krause, A. Wood–plastic composites as potential applications of recycled plastics of electronic waste and recycled particleboard. *Journal of Cleaner Production*, 121:176–185, 2016.
- [244] Son, J., Kim, H.-J., and Lee, P.-W. Role of paper sludge particle size and extrusion temperature on performance of paper sludge–thermoplastic polymer composites. *Journal of Applied Polymer Science*, 82(11):2709–2718, 2001.
- [245] Son, J., Yang, H.-S., and Kim, H.-J. Physico-mechanical properties of paper sludge-thermoplastic polymer composites. *Journal of Thermoplastic Composite Materials*, 17(6):509–522, 2004.

- [246] Soucy, J., Koubaa, A., Migneault, S., and Riedl, B. Chemical composition and surface properties of paper mill sludge and their impact on high density polyethylene (HDPE) composites. *Journal of Wood Chemistry and Technology*, 36(2):77–93, 2016.
- [247] Sperling, L. H. *Introduction to physical polymer science*. John Wiley & Sons, 2015.
- [248] Sridhar, I., Adie, P. P., and Ghista, D. N. Optimal design of customised hip prosthesis using fiber reinforced polymer composites. *Materials & Design*, 31(6):2767–2775, 2010.
- [249] Srivastava, V. K. and Pawar, A. G. Solid particle erosion of glass fibre reinforced flyash filled epoxy resin composites. *Composites Science and Technology*, 66(15):3021–3028, 2006.
- [250] Sumita, M., Shizuma, T., Miyasaka, K., and Ishikawa, K. Effect of reducible properties of temperature, rate of strain, and filler content on the tensile yield stress of nylon 6 composites filled with ultrafine particles. *Journal of Macromolecular Science, Part B: Physics*, 22(4):601–618, 1983.
- [251] Tagliavia, G., Porfiri, M., and Gupta, N. Analysis of flexural properties of hollow-particle filled composites. *Composites Part B: Engineering*, 41(1):86–93, 2010.
- [252] Takei, T., Hatta, H., and Taya, M. Thermal expansion behavior of particulate-filled composites I: single reinforcing phase. *Materials Science and Engineering: A*, 131(1):133–143, 1991.
- [253] Teixeira, S., Moreira, M., Lima, A. P., Santos, L. S., Rocha, B. M. D., Lima, E. S. D., da Costa, R. A., da Silva, A. L. N., Rocha, M. C., and Coutinho, F. Composites of high density polyethylene and different grades of calcium carbonate: mechanical, rheological, thermal, and morphological properties. *Journal of Applied Polymer Science*, 101(4):2559–2564, 2006.
- [254] Torkashvand, A. M., Haghghat, N., and Shadparvar, V. Effect of paper mill lime sludge as an acid soil amendment. *Scientific Research and Essays*, 5(11):130–1306, 2010.
- [255] Tserki, V., Zafeiropoulos, N. E., Simon, F., and Panayiotou, C. A study of the effect of acetylation and propionylation surface treatments on natural fibres. *Composites Part A: applied science and manufacturing*, 36(8):1110–1118, 2005.
- [256] Tserki, V., Matzinos, P., and Panayiotou, C. Novel biodegradable composites based on treated lignocellulosic waste flour as filler. Part II. Development of biodegradable composites using treated and compatibilized waste flour. *Composites Part A: Applied Science and Manufacturing*, 37(9):1231–1238, 2006.
- [257] Van Suchtelen, J. Product properties: a new application of composite materials. *Philips Res. Rep*, 27(1):28–37, 1972.

- [258] Velmurugan, R. and Manikandan, V. Mechanical properties of palmyra/glass fiber hybrid composites. *Composites Part A: applied science and manufacturing*, 38(10):2216–2226, 2007.
- [259] Verma, D., Gope, P. C., Shandilya, A., Gupta, A., and Maheshwari, M. K. Coir fibre reinforcement and application in polymer composites: A review. *Journal of Material & Environment Science*, 4(2):263–276, 2013.
- [260] Wang, J., Gu, M., Songhao, B., and Ge, S. Investigation of the influence of MoS<sub>2</sub> filler on the tribological properties of carbon fiber reinforced nylon 1010 composites. *Wear*, 255(1-6):774–779, 2003.
- [261] Wang, M.-J. The role of filler networking in dynamic properties of filled rubber. *Rubber chemistry and technology*, 72(2):430–448, 1999.
- [262] Wiegand, P. S. and Unwin, J. P. Alternative management of pulp and paper industry solid wastes. *Tappi journal*, 77(4):91–97, 1994.
- [263] Willett, J. L. Mechanical properties of LDPE/granular starch composites. *Journal of Applied Polymer Science*, 54(11):1685–1695, 1994.
- [264] Wong, K. J., Yousif, B. F., and Low, K. O. The effects of alkali treatment on the interfacial adhesion of bamboo fibres. *Proceedings of the Institution of Mechanical Engineers, Part L: Journal of Materials: Design and Applications*, 224(3):139–148, 2010.
- [265] Wu, C.-S. Improving polylactide/starch biocomposites by grafting polylactide with acrylic acid—characterization and biodegradability assessment. *Macromolecular Bioscience*, 5(4):352–361, 2005.
- [266] Yadav, A., Srivastava, V. K., and Gopal, V. Flexural and impact characterization of wheat flour reinforced epoxy composites treated with saline water. *Materials Today: Proceedings*, 5(2):5792–5801, 2018.
- [267] Yamamoto, I., Higashihara, T., and Kobayashi, T. Effect of silica-particle characteristics on impact/usual fatigue properties and evaluation of mechanical characteristics of silica-particle epoxy resins. *JSME International Journal Series A Solid Mechanics and Material Engineering*, 46(2):145–153, 2003.
- [268] Yang, H.-S., Kim, H.-J., Park, H.-J., Lee, B.-J., and Hwang, T.-S. Water absorption behavior and mechanical properties of lignocellulosic filler–polyolefin bio-composites. *Composite Structures*, 72(4):429–437, 2006.
- [269] Yang, H.-S., Kim, H.-J., Park, H.-J., Lee, B.-J., and Hwang, T.-S. Effect of compatibilizing agents on rice-husk flour reinforced polypropylene composites. *Composite Structures*, 77(1):45–55, 2007.
- [270] Yang, S., Bai, S., and Wang, Q. Morphology, mechanical and thermal oxidative aging properties of HDPE composites reinforced by nonmetals recycled from waste printed circuit boards. *Waste management*, 57:168–175, 2016.

- [271] Yang, X., Wang, W., and Huang, H. Resistance of paper mill sludge/wood fiber/high-density polyethylene composites to water immersion and thermotreatment. *Journal of Applied Polymer Science*, 132(11):1–7, 2015.
- [272] Yao, F., Wu, Q., Lei, Y., and Xu, Y. Rice straw fiber-reinforced high-density polyethylene composite: Effect of fiber type and loading. *Industrial crops and products*, 28(1):63–72, 2008.
- [273] Yao, Z., Xia, M., Ge, L., Chen, T., Li, H., Ye, Y., and Zheng, H. Mechanical and thermal properties of polypropylene (PP) composites filled with  $\text{CaCO}_3$  and shell waste derived bio-fillers. *Fibers and Polymers*, 15(6):1278–1287, 2014.
- [274] Yatigala, N. S., Bajwa, D. S., and Bajwa, S. G. Compatibilization improves physico-mechanical properties of biodegradable biobased polymer composites. *Composites Part A: Applied Science and Manufacturing*, 107:315–325, 2018.
- [275] Yellishetty, M., Karpe, V., Reddy, E. H., Subhash, K. N., and Ranjith, P. G. Reuse of iron ore mineral wastes in civil engineering constructions: A case study. *Resources, Conservation and Recycling*, 52(11):1283–1289, 2008.
- [276] Yildiz, Ü. C., Yildiz, S., and Gezer, E. D. Mechanical properties and decay resistance of wood–polymer composites prepared from fast growing species in Turkey. *Bioresource Technology*, 96(9):1003–1011, 2005.
- [277] Yu, T., Jiang, N., and Li, Y. Study on short ramie fiber/poly (lactic acid) composites compatibilized by maleic anhydride. *Composites Part A: Applied Science and Manufacturing*, 64:139–146, 2014.
- [278] Zadeh, K. M., Inuwa, I. M., Arjmandi, R., Hassan, A., Almaadeed, M., Mohamad, Z., and Khanam, P. N. Effects of date palm leaf fiber on the thermal and tensile properties of recycled ternary polyolefin blend composites. *Fibers and Polymers*, 18(7):1330–1335, 2017.
- [279] Zahran, R. R., El-Latif, A., Mahmoud, M., Konsowa, A. E.-A. H., and Awwad, M. Development of isotropic compatible HDPE/PP blends for structural applications. *Journal of applied polymer science*, 115(3):1407–1418, 2010.
- [280] Zhang, X. M. and Aji, A. Oriented structure of PP/LLDPE multilayer and blends films. *Polymer*, 46(10):3385–3393, 2005.
- [281] Zhang, Y., Zhang, A., Zhen, Z., Lv, F., Chu, P. K., and Ji, J. Red mud/polypropylene composite with mechanical and thermal properties. *Journal of Composite Materials*, 45(26):2811–2816, 2011.
- [282] Zhao, X., Li, R. K. Y., and Bai, S.-L. Mechanical properties of sisal fiber reinforced high density polyethylene composites: effect of fiber content, interfacial compatibilization, and manufacturing process. *Composites Part A: Applied Science and Manufacturing*, 65:169–174, 2014.

- [283] Zhou, B., Ji, X., Sheng, Y., Wang, L., and Jiang, Z. Mechanical and thermal properties of poly-ether ether ketone reinforced with  $\text{CaCO}_3$ . *European Polymer Journal*, 40(10):2357–2363, 2004.
- [284] Zhou, Z., Xu, M., Yang, Z., Li, X., and Shao, D. Effect of maleic anhydride grafted polyethylene on the properties of chopped carbon fiber/wood plastic composites. *Journal of Reinforced Plastics and Composites*, 33(13):1216–1225, 2014.
- [285] Zou, Y., Wang, L., Zhang, H., Qian, Z., Mou, L., Wang, J., and Liu, X. Stabilization and mechanical properties of biodegradable aliphatic polyestamide and its filled composites. *Polymer degradation and stability*, 83(1):87–92, 2004.
- [286] Zuiderduin, W., Westzaan, C., Huetink, J., and Gaymans, R. Toughening of polypropylene with calcium carbonate particles. *Polymer*, 44(1):261–275, 2003.