

TABLE OF CONTENTS

<i>Subject</i>	<i>Page No.</i>
Abstract	i - vi
List of Figures	vii - xii
List of Tables	xiii - xv
List of Abbreviations and Symbols	xvi - xix
<u>Chapter 1</u>	1.1 - 1.11
Introduction	
1.1 Introduction	1.1 - 1.6
1.2 Problem Statement	1.6
1.3 Objectives	1.7
References	1.8 - 1.11
<u>Chapter 2</u>	2.1 - 2.54
Review of literature	
2.1 Structure of lignocellulosic biomass (LCB) and its components	2.1 - 2.2
2.2 Pretreatment of LCB: necessity	2.2 - 2.3
2.2.1 Physical pretreatments	2.3
2.2.1.1 Milling	2.3 - 2.4
2.2.1.2 Microwave-assisted size reduction	2.4 - 2.5
2.2.1.3 Extrusion	2.5 - 2.6
2.2.1.4 Ultrasonication	2.6 - 2.7
2.2.2 Chemical pretreatments	2.7
2.2.2.1 Alkali pretreatment	2.7 - 2.8
2.2.2.2 Acid pretreatment	2.8 - 2.9
2.2.2.3 Ionic Liquids	2.9 - 2.11
2.2.2.4 Organosolv process	2.11
2.2.2.5 Deep eutectic solvents	2.11 - 2.12
2.2.3 Physicochemical pretreatments	2.12
2.2.3.1 Steam explosion	2.12 - 2.13
2.2.3.2 Ammonia fiber explosion (AFEX)	2.13 - 2.14
2.2.3.3 CO ₂ Explosion pretreatment	2.14 - 2.15
2.2.3.4 Liquid hot water (LHW)	2.15 - 2.16
2.2.4 Biological pretreatment	2.16

2.3	Glucose production from LCB	2.17
2.4	HMF synthesis: An overview	2.17 - 2.19
2.5	Solvent effects towards glucose to HMF production	2.19
2.5.1	Water	2.19 - 2.20
2.5.2	Organic solvents	2.20 - 2.22
2.5.3	Ionic Liquids (ILs)	2.22 - 2.24
2.5.4	Biphasic solvents	2.24 - 2.25
2.5.5	Mixed solvents	2.25 - 2.26
2.6	Heterogeneous catalysts for the dehydration of carbohydrates into HMF	2.26 - 2.27
2.6.1	Metal oxides	2.27 - 2.29
2.6.2	Silica-based catalysts	2.29 - 2.30
2.6.3	Heteropoly acids	2.30 - 2.31
2.6.4	Carbon-based solid acids	2.31 - 2.32
2.6.5	Meta phosphates	2.32 - 2.33
2.7	Density functional theory (DFT) study of glucose dehydration to HMF	2.33 - 2.35
References		2.36 - 2.54

Chapter 3

3.1 - 3.35

Isolation of cellulose from lignocellulosic feedstocks (*Saccharum spontaneum* and Banana agrowastes) using an integrated pretreatment technique: Process optimization and structural characterization

3.1	Introduction	3.1 - 3.3
3.2	Materials and methods	3.3
3.2.1	Materials and chemicals	3.3
3.2.2	Preparation of raw material	3.3 - 3.4
3.2.3	Cellulose isolation from the untreated materials	3.4 - 3.5
3.2.4	Optimizing acid hydrolysis variables using Taguchi design	3.5 - 3.6
3.2.5	Characterization	3.6
3.2.5.1	Chemical composition	3.6 - 3.7
3.2.5.2	Yield and Degree of Polymerization	3.7
3.2.5.3	Microstructural characterizations	3.7 - 3.8
3.2.5.4	Thermogravimetric analysis (TGA)	3.8
3.2.5.5	Morphological analysis	3.8

3.3	Results and discussion	3.8
3.3.1	Isolation of cellulose and chemical composition	3.8 - 3.12
3.3.2	FTIR spectroscopy analysis	3.12 - 3.13
3.3.3	X-ray diffraction analysis	3.14 - 3.16
3.3.4	Thermogravimetric analysis (TGA)	3.16 - 3.18
3.3.5	Morphological analysis	3.18 - 3.19
3.3.6	Optimization of acid hydrolysis treatment using Taguchi design	3.19 - 3.27
3.4	Conclusion	3.27 - 3.28
	References	3.29 - 3.35
	<u>Chapter 4</u>	4.1 - 4.34
	Optimization of enzymatic hydrolysis of cellulose extracted from Saccharum spontaneum and banana peduncle using RSM, ANN, and ANFIS statistical tools	
4.1	Introduction	4.1 - 4.3
4.2	Materials and methods	4.3
4.2.1	Materials and chemicals	4.3
4.2.2	Enzymatic hydrolysis	4.3 - 4.4
4.2.3	Optimizing enzymatic hydrolysis variables using RSM	4.4 - 4.5
4.2.4	Optimizing enzymatic hydrolysis variables using ANN	4.5 - 4.6
4.2.5	Optimizing enzymatic hydrolysis variables using ANFIS	4.6 - 4.7
4.2.6	Model performance indices	4.7 - 4.8
4.2.7	Product analysis	4.9
4.3	Results and discussion	4.9
4.3.1	Optimization of enzymatic hydrolysis using RSM	4.9 - 4.18
4.3.2	Optimization of enzymatic hydrolysis using ANN	4.18 - 4.20
4.3.3	Optimization of enzymatic hydrolysis using ANFIS	4.20 - 4.24
4.3.4	Performance assessment of predictive ability of RSM, ANN and, ANFIS models	4.24 - 4.26
4.3.5	Experimental validation of RSM, ANN and, ANFIS optimal predictive outputs	4.26 - 4.27
4.3.6	Comparison between the glucose yield obtained from this work to that of previous work	4.28
4.4	Conclusion	4.29

References	4.30 - 4.36
<u>Chapter 5</u>	5.1 - 5.49
Synthesis of magnetically recoverable polyaniline-based bifunctional solid-acid catalyst for the catalytic transformation of biomass-derived glucose into hydroxymethylfurfural	
5.1 Introduction	5.1 - 5.2
5.2 Experimental section	5.2
5.2.1 Materials	5.2
5.2.2 Synthesis of Fe ₃ O ₄ nanoparticles	5.3
5.2.3 Synthesis of Fe ₃ O ₄ @sulfonated polyaniline	5.3 - 5.4
5.2.4 Catalysts characterization	5.4 - 5.5
5.2.5 Reaction procedure using Multivariate Experimental Design	5.6 - 5.7
5.2.6 Substrate and product analysis	5.7 - 5.8
5.2.7 Catalyst reusability test	5.8
5.2.8 Computational details	5.8
5.3 Results and discussion	5.8
5.3.1 Comparison of catalytic activity of different synthesized catalysts and in different solvents based on HMF yield	5.8 - 5.11
5.3.2 Catalysts characterization	5.11 - 5.20
5.3.3 Optimization of reaction parameters for HMF production using Multivariate Experimental Design	5.21 - 5.29
5.3.4 Experimental validation of RSM and ANN predictive outputs and assessment of catalytic performance of 15-Fe ₃ O ₄ @SPAN-9/3 with lignocellulose (<i>Saccharum spontaneum</i> and banana peduncle) derived glucose	5.29 - 5.31
5.3.5 Recyclability and stability of the catalyst	5.32 - 5.33
5.3.6 Probable mechanism for the catalytic dehydration of glucose to HMF over Fe ₃ O ₄ @SPAN based catalyst	5.33 - 5.34
5.4 Comparison of activity of 15-Fe ₃ O ₄ @SPAN-9/3 with other reported catalyst	5.34 - 5.36
5.5 Computational study on glucose conversion to HMF	5.36 - 5.42
5.5 Conclusion	5.42
References	5.43 - 5.49

Chapter 6		6.1 - 6.44
Design of acid bifunctionality (Lewis and Brønsted) on mesoporous silicate, KIT-6 for the conversion of biomass-derived glucose into hydroxymethylfurfural		
6.1	Introduction	6.1 - 6.3
6.2	Experimental section	6.3
	6.2.1 Materials	6.3
	6.2.2 Synthesis of mesoporous Nb-KIT-6	6.3
	6.2.3 Preparation of functionalized mesoporous Nb-KIT-6	6.4
	6.2.4 Catalysts characterization	6.5 - 6.6
	6.2.5 Reaction procedure using Multivariate Experimental Design	6.6 - 6.7
	6.2.6 Substrate and product analysis	6.7 - 6.8
	6.2.7 Catalyst reusability test	6.8
6.3	Results and discussion	6.8
	6.3.1 Comparison of catalytic activity of different synthesized catalysts and in different solvents based on HMF yield	6.8 - 6.11
	6.3.2 Catalysts characterization	6.12 - 6.21
	6.3.3 Optimization of reaction parameters for HMF production using Multivariate Experimental Design	6.21 - 6.30
	6.3.4 Experimental validation of RSM and ANN predictive outputs and assessment of the catalytic performance of Nb-KIT-6(20)-SO ₃ H with lignocellulose (<i>Saccharum spontaneum</i> and banana peduncle) derived glucose	6.30 - 6.32
	6.3.5 Recyclability and stability of the catalyst	6.32 - 6.33
	6.3.6 Probable mechanism for the catalytic dehydration of glucose to HMF over Nb-KIT-6(20)-SO ₃ H catalyst	6.33 - 6.35
6.4	Comparison of the activity of Nb-KIT-6(20)-SO ₃ H with other reported silica-based catalyst	6.35 - 6.36
6.5	Conclusion	6.36 - 6.37
References		6.38 - 6.44

<u>Chapter 7</u>	7.1 - 7.6
Conclusion and future perspective	
7.1 Summary and conclusions	7.1 - 7.4
7.2 Future prospects of the current work	7.4 - 7.6
List of publications	xx - xxi
Conferences and Symposiums attended	xxii - xxiii