

CONTENTS

| | |
|------------------------------|----------------------|
| <i>Abstract</i> | <i>i - iii</i> |
| <i>Declarations</i> | <i>iv</i> |
| <i>Certificates</i> | <i>v-vi</i> |
| <i>Acknowledgements</i> | <i>vii - viii</i> |
| <i>Contents</i> | <i>xi-xii</i> |
| <i>List of tables</i> | <i>xiii - xiv</i> |
| <i>List of figures</i> | <i>xv - xxvii</i> |
| <i>List of abbreviations</i> | <i>xxviii - xxiv</i> |

CHAPTER 1: Introduction

| | |
|--|-------|
| 1.1 Introduction: Energy storage | 1-2 |
| 1.2 Supercapacitor | 2-3 |
| 1.2.1 Electric double layer capacitor (EDLC) | 3-5 |
| 1.2.2 Pseudocapacitor | 5 |
| 1.2.3 Hybrid capacitor | 6 |
| 1.3 Battery | 6-8 |
| 1.3.1 Aluminum ion battery | 7 |
| 1.3.2 Aqueous electrolyte | 7-8 |
| 1.4 Conducting polymer | 8-10 |
| 1.5 Graphene | 10-11 |
| 1.6 Molybdenum disulphide | 11-12 |
| 1.7 Swift heavy ion irradiation | 13-14 |
| 1.8 Mxene | 14-15 |
| 1.9 Lithium iron phosphate | 15-17 |
| 1.10 References | 17-26 |

CHAPTER 2: Ternary nanocomposite of molybdenum disulfide, reduced graphene oxide and poly(3,4-ethylenedioxythiophene) for supercapacitor

| | |
|---|-------|
| 2.1 Introduction | 27-28 |
| 2.2 Experimental | 28-31 |
| 2.2.1 Materials | 29 |
| 2.2.2 Synthesis of MoS ₂ -rGO structures | 29 |

| | |
|---|-------|
| 2.2.3 Synthesis of MoS ₂ -rGO/PEDOTNPs ternary nanocomposite | 29-30 |
| 2.2.4 Structural and morphological characterizations | 30 |
| 2.2.5 Electrochemical measurements | 30-31 |
| 2.3 Results and discussion | 31-59 |
| 2.3.1 Schematic representation | 31-32 |
| 2.3.2 X-ray diffraction analysis | 32-34 |
| 2.3.3 Morphological analysis (Scanning electron microscope and Transmission electron microscope) | 34-37 |
| 2.3.4 Thermogravimetric analysis | 37-39 |
| 2.3.5 Raman analysis | 39-41 |
| 2.3.6 X-ray Photoelectron Spectroscopy analysis | 41-43 |
| 2.3.7 Specific surface area and porosity analysis | 43-45 |
| 2.3.8 Contact angle measurement | 45-47 |
| 2.4 Electrochemical characterization | 47-59 |
| 2.4.1 Electrochemical measurements of electrodes | 47-54 |
| 2.4.2 Electrochemical measurements of symmetric supercapacitor | 54-59 |
| 2.5 Conclusion | 59-60 |
| 2.6 References | 60-68 |

**CHAPTER 3: Layer-by-layer self-assembly of MoS₂, rGO and polypyrrole
nanotubes for enhanced electrochemical performance of
supercapacitor**

| | |
|--|-------|
| 3.1 Introduction | 69 |
| 3.2 Experimental | 69-71 |
| 3.2.1 Materials | 69-70 |
| 3.2.2 Exfoliation of MoS ₂ , synthesis of graphene oxide (GO) nanosheets and preparation of MoS ₂ -rGO structures | 70 |
| 3.2.3 Synthesis of MoS ₂ -rGO/PPyNTs ternary nanocomposites | 70 |
| 3.2.4 Structural and morphological characterizations | 70 |
| 3.2.5 Electrochemical measurements | 71 |
| 3.3 Results and discussion | 71-86 |
| 3.3.1 Schematic representation | 71-72 |
| 3.3.2 Zeta potential measurements | 71-73 |

| | |
|--|-------|
| 3.3.3 Scanning Electron Microscopy | 73 |
| 3.3.4 Transmission Electron Microscopy | 74 |
| 3.3.5 X-ray diffraction analysis | 74-76 |
| 3.3.6 Thermogravimetric analysis | 76-77 |
| 3.3.7 Brunauer-Emmett-Teller measurements | 77 |
| 3.4 Electrochemical characterization | 78-86 |
| 3.4.1 Electrochemical measurements of electrodes | 78-84 |
| 3.4.2 Electrochemical measurements of symmetric supercapacitor | 84-86 |
| 3.5 Conclusion | 87 |
| 3.6 References | 87-89 |

CHAPTER 4: Electrochemical study on ion beam modified ternary composite of molybdenum disulfide, -reduced graphene oxide and / polypyrrole nanotubes

| | |
|---|---------|
| 4.1 Introduction | 90-92 |
| 4.2 Experimental | 92-95 |
| 4.2.1 Materials | 92-93 |
| 4.2.2 Synthesis of MoS ₂ -rGO/PPyNTs composite | 93 |
| 4.2.3 Swift heavy ion irradiation on MoS ₂ -rGO/PPyNTs ternary nanocomposite | 93-94 |
| 4.2.4 Structural and morphological characterizations | 94 |
| 4.2.5 Electrochemical measurements | 94-95 |
| 4.3 Results and discussion | 95-118 |
| 4.3.1 Field Emission Scanning Electron Microscopy | 95-96 |
| 4.3.2 X-ray diffraction analysis | 96-98 |
| 4.3.3 Fourier transforms infrared spectroscopy | 98-100 |
| 4.3.4 Raman spectroscopy analysis | 100-103 |
| 4.3.5 Contact angle analysis | 103-105 |
| 4.3.6 Electrochemical behaviour of the electrodes towards redox species | 106-109 |
| 4.3.7 Cyclic Voltammetry | 109-110 |
| 4.3.8 Galvanostatic charge-discharge | 110-116 |
| 4.3.9 Electrochemical impedance spectroscopy analysis | 116-118 |

| | |
|----------------|---------|
| 4.4 Conclusion | 118 |
| 4.5 References | 119-123 |

CHAPTER 5: Electrochemical exfoliation of Ti_3AlC_2 MAX phase and unusual Al^{3+} ion storage in aqueous electrolyte

| | |
|--|---------|
| 5.1 Introduction | 124-125 |
| 5.2 Experimental | 125-126 |
| 5.2.1 Materials | 125 |
| 5.2.2 Electrode preparation | 125 |
| 5.2.3 Electrochemical exfoliation process | 125 |
| 5.2.4 Structural and morphological characterizations | 125 |
| 5.2.5 Electrochemical measurements | 126 |
| 5.3 Results and discussion | 126-140 |
| 5.4 Conclusion | 141 |
| 5.5 References | 141-143 |

CHAPTER 6: Al^{3+} ion storage behavior of $LiFePO_4$ in aqueous electrolyte

| | |
|---|---------|
| 6.1 Introduction | 144 |
| 6.2 Experimental | 144-145 |
| 6.2.1 Materials | 144 |
| 6.2.2 Electrode preparation and electrochemical measurement | 145 |
| 6.2.3 Structural and morphological characterizations | 145 |
| 6.3 Results and discussion | 145-158 |
| 6.4 Conclusion | 158 |
| 6.5 References | 158-160 |

CHAPTER 7: Conclusion and future outlook

| | |
|--------------------|---------|
| 7.1 Conclusion | 161-165 |
| 7.2 Future outlook | 165 |