DECLARATION

I, hereby, declare that the thesis entitled "Design of smartphone-based analytical tools for detection and analysis of chemicals, heavy metals and biological contaminants in water", submitted to the School of Sciences, Tezpur University (TU), in partial fulfillment of the requirements for the award of the Doctor of Philosophy in Physics, has been carried out by me at the Department of Physics, TU, Assam, India-784028, under the supervision of **Prof. Pabitra Nath**. The contents of this work is original except where specific reference is made to the works of others and has not been submitted in whole or in part for consideration for any other degree or qualification in this or any other University or institute.

Diganta Hatiboruah

Date



TEZPUR UNIVERSITY (A central University established by an Act of Parliament) DEPARTMENT OF PHYSICS

Tezpur-784028, Assam, India

CERTIFICATE OF THE PRINCIPAL SUPERVISOR

This is to certify that the thesis entitled "Design of smartphone-based analytical tools for detection and analysis of chemicals, heavy metals and biological contaminants in water", submitted to the School of Sciences, Tezpur University in partial fulfillment for the award of degree of Doctor of Philosophy in Physics, is a record of research work carried out by Mr. Diganta Hatiboruah under my guidance and supervision.

All kinds of support received by him from various sources have been duly acknowledged. No part of this thesis has been submitted elsewhere for award of any other degree.

> Date: Place:

Prof. Pabitra Nath Department of Physics Email: pnath@tezu.ernet.in Ph. no. +91-3712-275575 Fax. +91-3712-267006



TEZPUR UNIVERSITY (A central University established by an Act of Parliament) DEPARTMENT OF PHYSICS

Tezpur-784028, Assam, India

CERTIFICATE OF THE EXTERNAL EXAMINER

This is to certify that the thesis entitled "Design of smartphone-based analytical tools for detection and analysis of chemicals, heavy metals and biological contaminants in water", submitted by Diganta Hatiboruah to the School of Sciences, Tezpur University in partial fulfillment for the award of degree of Doctor of Philosophy in Physics, has been examined by us on/...... and found to be satisfactory.

Prof. Mrinal Kumar Das Head of the department Department of Physics Tezpur University, Napaam 785700 External examiner

ACKNOWLEDGMENT

This work is not just the output of my understanding of the subject but the outcome of the advice, guidance, encouragement, cooperation and support of many individuals, including my parents, family, friends and well-wishers. Herein I take an opportunity to express my heartfelt gratitude to everyone who have directly or indirectly contributed and helped me through with the successful completion of this journey.

At the onset, I deem it a privilege to express my deep sense of gratitude and heartfelt thanks to my research supervisor **Prof. Pabitra Nath**, Department of Physics, Tezpur University. I am highly grateful for his encouragement, invaluable guidance and constant supervision from the beginning to the end of this research work. His dynamic personality, insightful nature and a positive approach towards life had a great deal of impact on my life and life-choices.

I wish to express my appreciation and thanks to my DC members **Prof. Gazi A. Ahmed** and **Dr. Nima D. Namsa** for their guidance, support and suggestions from time to time without whom this thesis would have not seen the light of the day.

I express my gratitude to all the faculty members, research scholars, seniors and juniors of the entire Department of Physics, all the technical and non-technical staffs of Tezpur University (TU) fraternity for their unprecedented help. I am thankful to **Prof. Mrinal Kumar Das**, HoD, Department of Physics and **Prof. Nilakshi Das** (former HoD, Department of Physics) for their support in the department in any circumstances. I owe special gratitude to **Prof. Vinod Kumar Jain**, Vice-Chancellor, Tezpur University for giving me the opportunity and facility to carry out my research work smoothly inside the campus. I acknowledge BIRAC-SRISTI, New Delhi and Tezpur University (Research and Innovation Grant), for providing the necessary financial help during the PhD period.

At this juncture, it is pertinent to acknowledge **Prof.** A. **Pradhan**, Department of Photonics, IIT Kanpur; **Dr. U. Bora** and **Dr. P. Bharali**, Department of Chemistry, Tezpur University; **Prof. S. K. Ray** and **Prof. M. Mandal**, Department of Molecular Biology and Biotechnology, Tezpur University; **Dr. K. U. Ahmed** and **Mr. P. Kalita**, Department of Civil Engineering, Tezpur University; **Prof. P. Misra**, Department of Food Engineering and Technology, Tezpur

University and **Prof.** D. Deka, Department of Energy, Tezpur University. I am greatful for their suggestions, guidance and availability round the clock to help me out always. Also to mention Shivam, Monica, Dama Di, Porag Da, Doljit Da for collaborating with me at various stages of my doctoral research carrier. I would like to thank each and one of them for their incessant help and support during this journey.

I wholeheartedly thank my lab mates *Sibashis Da*, *Iftak Da*, *Naba Da*, *Rabha, Sritam, Priyanka, Deepjyoti, Biprav* and *Rupam* for their constant encouragement and cooperation and for making this journey a pleasant one. Also to mention *Narayan Da*, *Patir Da*, *Ratan Da*, *Ripu Da* from Department of Physics, who were always there in times of need.

I consider myself lucky to have warm-hearted friends and seniors like **Biswa Da**, **Roket Da**, **Debasish da**, **Bichitra Da**, **Ankur Da**, **Animesh Da**, **Sudorshon Da**, **Ansuman Da**, **Niran**, **Olog**, **Tonmoy**, **Prankrisno**, **Sukla**, **Nandy**, **Rituporno**, **Aftab**, **Lavina**, **Nayana**, **Jatin**, **Boisyo**, **Prabhakar**, **Bhowel**, **Sudhangshu**, **Suku**, **Hiya**, **Nimi**, **Prantika**, **Debango**, **Debabrat**, **Bijoy**, **Nishant**, **Bishal**. I am extremely thankful to them for giving me a helping hand always.

A special thanks to *Tapu*, *Malua*, *Babu*, *Abhisekh*, *Dipankar*, *Dikshi* (*puali*), *Gori* and *Pori* for accepting nothing less than excellence from me and for staying with me in my toughest times, who were always there for me whenever I needed them. This would not have been possible without their love, support and constant motivation.

I convey my deepest acknowledgement to my pillars of strength - my family -*Mr. Kanak Hatiboruah* (*Deuta*) and *Mrs. Prity Hatiboruah* (*Maa*) whose blessings have brought me closer to all the joys of my life. I am grateful to my elder sisters *Sikha Hatiboruah* (*mainu*), *Pinky Hatiboruah* (*maini*), my dearest nephew *Ton* for their impassioned love and unfailing support.

I am grateful to the Almighty for providing me this life to accomplish this phase in my lifetime and to meet all the wonderful people acknowledged above.

(Diganta Hatiboruah)

	5.5	Estimation of sulphate and chloride ions	
		concentration using the photometric mode of the designed platform . 88	
	5.6	Estimation of sulphate and chloride ions	
		concentration using the nephelometric mode of the designed platform 89	
	5.7	Performance evaluation of the sensor in	
		presence of other interfering elements	
	5.8	Analysis of sensor response with field-collected water samples \ldots 93	
	5.9	Summary 94	:
	Refe	erences $\ldots \ldots $	
6	STV	IULTANEOUS PHOTOMETRIC AND FLUORESCENCE BASEI	`
0		NSING FOR DETECTION OF ZINC IONS IN WATER 99	
	6.1	Introduction	
	6.2	Design of the proposed analytical platform for simultaneous sensing	
	0.2	in photometric and	
		fluorescence mode	
	6.3	Development of the Android application for simultaneous measure-	
	0.0	ment of absorbance and fluorescence spectrum	
	6.4	Wavelength calibration	
	6.5	Materials and methods	
	0.0	6.5.1 Preparation of the water sample for selective detection of zinc	
		ions	
		6.5.2 Spectrometric analysis of the prepared student samples with	
		varying zinc concentration	
	6.6	Sensor calibration	
		6.6.1 Calibration in the photometric mode of the designed sensor . 108	
		6.6.2 Calibration in the fluorescence mode of the designed sensor . 109	,
	6.7	Performance evaluation of the sensor in	
		presence of other interfering elements	
	6.8	Performance evaluation of the sensor for field-collected water samples 111	
	6.9	Summary	
	Refe	erences	:
_	DD		
7		SIGN OF A UNIVERSAL 3D PRINTED HOLDER FOR SENS-	
		G AND IMAGING STUDIES IN ALL VARIANT SMART-	
		ONES 117	
	7.1	Introduction	

List of Figures

1.1	.1 Schematic representation of increasing number of research articles	
	in the field of designing the smartphone-based sensing and imaging	
	platforms. Data are taken from the 'Web of Science' database on	
	10th May 2022 [47]	

8

9

1.2	The development of different smartphone-based analytical platforms;
	(a) a smartphone based opto-sensing platform, figure reproduced
	from $[52]$ with permission from American Chemical Society, (b) a
	smartphone turbidimeter, figure reproduced from [53] with permis-
	sion from <i>Optica Publishing Group</i> , (c) an evanescent wave coupled
	smartphone spectrometer, figure reproduced from [54] with permis-
	sion from <i>IEEE Publishing Group</i> , (d) a smartphone based fluores-
	cence spectrometer, figure reproduced from $[55]$ with permission form
	American Chemical Society and (e) a smartphone-based microscope,
	figure reproduced from $[56]$ with permission from Royal Microscopical
	Society.

1.3 The development of smartphone-based analytical platforms for heavy metal detection in water; (a) a smartphone based opto-mechanical platform to detect mercury ions, figure reproduced from [83] with permission from American Chemical Society, (b) a smartphone read-out device for chromium ion estimation, figure reproduced from [84] with permission from Royal Society of Chemistry, and (c) a dual-mode smartphone spectrometer used in zinc ions estimation, figure reproduced from [85] with permission from SPIE Publishing Group. 13

The development of smartphone-based analytical platforms for esti-1.4mation of chemicals and minerals in water; (a) a smartphone based colorimeter to detect calcium ions, figure reproduced from [88] with permission from *Elsevier publishing group*. (b) a smartphone selfreferencing colorimeter for chlorine estimation, figure reproduced from [89] with permission from *Elsevier publishing group*, (c) a smartphone colorimeter to detect chlorine in water, figure reproduced from [90] with permission from *IEEE Publishing Group* and (d) a smartphone photometric fluoride level monitor, figure reproduced from [91] with permission from American Chemical Society. 15The development of smartphone-based analytical platforms for esti-1.5mation of physical properties of water; (a) a smartphone-based turbidimeter to measure turbidity of water, figure reproduced from [97] with permission from Royal Society of Chemistry, (b) a smartphone turbidity reader, figure reproduced from [98] with permission from Nature Publishing Group, and (c) schematic of a smartphone based refractive index reader, figure reproduced from [99] with permission from MDPI Publishing Group. 17The development of smartphone-based analytical platforms for detec-1.6tion of bio-contamination in water; (a) a smartphone based bacteria detector, figure reproduced from [59] with permission from IEEE Pub*lishing group*, (b) a smartphone assisted bacterial incubator, figure reproduced from [101] with permission from *Faculty of Biotechnology* and Food Sciences, and (c) a dual-mode smartphone tool for detection of total *coliform* and *E. coli*, figure reproduced from [102] with 192.1(a) Schematic representation of a conventional CMOS pixel array and (b) relative spectral sensitivity of a smartphone camera. 36 2.2(a) Illustrastration on the typical position of an ALS sensor embedded on a smartphone and (b) spectral sensitivity of a regular ALS, figure is reproduced from [15]. 38(a) 'Designer' window and (b) 'Block' window of the 'MIT App 2.3Inventor-2' platform. 392.4(a) Application flow chart for pre-calibrated mode of operation of a 40

3.1	(a) schematic and (b) photo-image of the designed smartphone fluo- rescence platform, and (c) cropped region of interest $(200 \times 200 \text{ pixel})$	
	of the captured image.	49
3.2	Screenshot of (a) pre-calibrated mode of operation and (b) in-field	
	calibration mode of operation of the developed Android application.	52
3.3	(a) Absorbance spectra of standard Hg^{2+} test samples with concen-	
	tration 0.00 ppm , 0.05 ppm , 0.10 ppm , 0.15 ppm , 0.30 ppm , 0.50 ppm	
	and 0.80 ppm [(i) to (vii)] measured with the standard UV-VIS spec-	
	trometer. (b) fluorescence spectra of the standard Hg^{2+} test samples	
	with concentration 0.00 ppm, 0.05 ppm, 0.10 ppm, 0.20 ppm, 0.25	
	ppm, 0.30 ppm, 0.40 ppm, 0.45 ppm, 0.50 ppm and 0.60 ppm [(i) to	
	(x)] recorded by the standard spectrometer. \ldots	55
3.4	(a) Calibration curve of the proposed platform obtained for standard	
	Hg^{2+} ion concentrations in water sample. (b) Cropped images of the	
	fluorescence emission signals recorded by the designed sensor for dif-	
	ferent concentration of Hg^{2+} ion in water samples. The error bar has	
	been obtained upon recording the signal response for 5 consecutive	
	measurements of each sample	56
3.5	${\rm Histogram\ representation\ of\ developed\ smartphone\ platform\ and\ stan-}$	
	dard spectrometer responses in presence of Fe^{2+} , Cu^{2+} , Zn^{2+} and	
	$\rm Mg^{2+}$ ions with concentration 56 ppm, 63 ppm, 65 ppm and 24 ppm	
	respectively in Hg^{2+} test sample. The error bar has been obtained	
	upon recording the signal response for 5 consecutive measurements	
	for each sample	58
3.6	Histogram representation of Hg^{2+} concentration in field collected wa-	
	ter sample measured by both smartphone platform and Atomic Ab-	
	sorption Spectrometer (AAS). The error bar represents the signal	
	response for 5 consecutive measurements of each sample measured	
	by both the tools	60
4.1	(a) Schematic of the designed smartphone nephelometer and (b)	
	photo-image of the 3D printed setup attached to the phone. $\ . \ . \ .$	66
4.2	Screenshots of the Android application that has been developed for	
	monitoring the growth kinetics of bacteria samples	67

4.3	Regression analysis of the designed sensor response while measuring turbidity level from different formazin standard samples. Error bar
	in the figure indicates the standard deviation in sensor responses 71
4.4	Comparison of the growth kinetics recorded by the standard spec-
	trophotometer and by the designed smartphone sensor for (a) $E. \ coli$
	and (b) <i>B. subtilis.</i> The three phases of the growth process for both
	the considered bacteria can be distinctly recorded by the designed
	sensor
4.5	Variation of cell populations (CFU/ml) vs. turbidity of $E \ coli$ bac-
	teria in the cultured medium. \ldots \ldots \ldots \ldots \ldots $$ 74
4.6	Histogram representation of turbidity measurements of five different
1.0	bacterial samples in three distinct dilutions
5.1	Schematic of the designed dual mode smartphone platform (a) pho-
	tometric mode and (b) turbidimetric mode, (c) and (d) photo-image
	of the 3D printed dual mode smartphone platform
5.2	Screenshot images of the custom developed Android application 86
5.3	Calibration curves and performance comparison of the designed tool
	with the laboratory instrument while measuring (a) sulphate and (b)
	chloride ions using the photometric mode
5.4	Calibration curve obtained for the standard formazin samples using
	the designed smartphone platform. $\dots \dots \dots$
5.5	Calibration curves and performance comparison of the designed tool
	with the laboratory instrument while measuring (a) sulphate and (b)
	chloride ions using the nephelometric mode
5.6	Histogram representation of designed smartphone platform responses
	in presence of K^+ , Ba^{2+} , NO^{2-} and PO_4^{3-} ions with concentration 10
	ppm, 2 ppm, 1 ppm and 0.1 ppm respectively in the standard sulphate
	and chloride samples
5.7	Histogram representation of (a) sulphate ion and (b) chloride ion con-
	centration in field-collected water samples that have been estimated
	using the UV-VIS spectrophotometer and the smartphone based sens-
	ing platform
6.1	(a) optical layout design and (b) photo-image of the 3D printed dual
	mode smartphone-based analytical platform
	· –

6.2	Screenshot images of the custom developed Android application (a) home screen of the app, (b) & (d) pre-calibrated settings for esti- mation of absorbance and fluorescence spectra, (c) & (e) calibration settings for estimation of absorbance and fluorescence spectra, (f) si- multaneous spectrophotometric and fluorescence based detection of
	zinc ions
6.3	Pixel to wavelength conversion of the designed sensing platform. (a) uncorrected spectra, (b) corrected spectra after estimating the correc- tion factor of the smartphone spectrometer, and (c) pixel vs. wave- length plot for three LEDs having peak emission wavelengths at 470
~ (nm, 525 nm and 636 nm
6.4	(a) Absorption spectra of gold nanoparticles (1 mM) and rhodamineB (0.05 mM), (b) absorption and (c) fluorescence spectra of AuNP-
	RhB mixture at varying concentrations of zinc ion in the medium 107
6.5	(a) Calibration curve of the photometric mode of the designed plat-
	form for standard Zn^{2+} samples mixed with RhB (0.05 mM) and
	AuNPs (1 mM) assay, (b) absorbance measured in the designed tool
	in comparison with a standard UV-VIS spectrophotometer data 109
6.6	(a) Fluorescence spectra of standard Zn^{2+} samples with RhB (0.05
	mM) and AuNPs (1 mM) mixture as obtained from the designed
	smartphone platform and (b) fluorescence responses of the designed
	tool in comparison with the standard laboratory spectrometer data 110
6.7	Responses of the designed smartphone platform were recoreded under
	both the sensing modes after adding Cu^{2+} , Mn^{2+} , Al^{3+} , Na^+ , Mg^{2+} ,
	Hg^{2+} and As^{3+} in the standard Zn^{2+} samples
6.8	Estimation of Zn^{2+} ions concentration in field-collected water samples
	using both the sensing modes (absorbance and fluorescence) of the
	designed smartphone tool
7.1	Illustration of the 3D drawing of the universal smartphone holder
	from the (a) isometric and (b) front view perspective
7.2	(a) Schematic of the optical layout design and (b) the 3D printed
	prototype of the dual mode colorimetric and fluorescence platform
	coupled to the smartphone using the universal phone holder 121

7.3	(a) Schematic of the optical layout design and (b) the 3D printed pro-
	to type of the microscopic imaging system coupled to the smartphone
	using the universal phone holder. $\ldots \ldots \ldots$
7.4	Illustrations of size and camera position of three different company-
	make smartphones, namely (a) Motorola One power, (b) Xiaomi
	Redmi K20 and (c) Samsung Galaxy C9 Pro
7.5	Transmitted intensity of rhodmine 6g with varying concentration as
	measured in the designed system using three different smartphones 126
7.6	Fluorescence intensity of rhodmine6g with varying concentration as
	measured in the designed colorimeter using three different smartphones. 127
7.7	Images of the (a) resolution target (b) intensity profile and (c) blood
	cells captured by a standard optical microscope and the smartphone
	microscope attached with three different smartphones such as Mo-
	torola, Xiaomi and Samsung respectively

List of Tables

2.1	Embedded sensors of smartphones and their usage
2.2	Characteristic parameters of four different smartphones which are
	used in the present thesis work
3.1	Characteristic parameters of the designed smartphone fluorometer 57
3.2	Analysis of field samples by the proposed smartphone sensor collected
	from different location in Assam, India
4.1	%RSD in estimating turbidity of <i>E. coli</i> bacterial samples \ldots 72
4.2	%RSD in estimating turbidity of <i>B. subtilis</i> bacterial samples \ldots 72
5.1	Figure of merits of the designed platform while measuring sulphate
	and chloride ions concentration in water
5.2	Performance comparison of the designed sensor with the works re-
	ported in the line of the present research
6.1	Estimation of %Recovery while investigating the field-collected wa-
	ter samples under both the sensing modalities of the designed smart-
	phone sensor
7.1	Characteristic sensor parameters obtained for the colorimetric mode
	of the designed colorimeter
7.2	Characteristic parameters obtained for the fluorescence mode sensing
	of the designed system

$List \ of \ abbreviations$

AAS	Atomic Absorption spectroscopy
AFS	Atomic Fluorescence Spectroscopy
ALS	Ambient Light Sensor
AMOLED	Active-Matrix Organic Light-Emitting-Diode
AuNP	Gold Nano-particles
BF	Bright-field
BIS	Bureau of Indian Standards
BL	Ball Lens
CAD	Computer-Aided Design
CCD	Charge-Coupled Devices
CFA	Color Filter Array
CFU	Colony Forming Unit
CMOS	Complementary Metal-Oxide Semiconductor
CPU	Central Processing Unit
CT	Computed Tomography
ELISA	Enzyme-Linked Immunosorbent Assay
EMR	Electro Magnetic Radiation
FDM	Fused Deposition Modeling
FRET	Fluorescence Resonance Energy Transfer
FWHM	Full Width Half Maximum
GPU	Graphics Processing Unit
GUI	Graphical User Interface
HPLC	High-Performance Liquid Chromatography
IF	Infrared Filter
IR	Infrared
LCD	Liquid Crystal Displays
LED	Light Emitting Diode
LSPR	Localized Surface Plasmon Resonance
MRI	Magnetic Resonance Imaging
MS	Mass Spectroscopy
MTCC	Microbial Type Culture Collection
MTF	Modulation Transfer Function
NA	Numerical Aperture

NTU	Nephelometric Turbidity Unit
OD	Optical Density
OS	Operating System
OTG	On-The-Go
PCX	Plano Convex
PIC	Photonic Integrated Circuit
PLA	Polylactide Acid
PoC	Point-of-Care
RAM	Random Access Memory
ROM	Read-Only Memory
rpm	Rotations per minute
SOP	Standard Operating Protocol
SPR	Surface Plasmon Resonance
TCC	Total Cell Count
UI	User Interface
USAF	United State Air Force
USB	Universal Serial Bus
US-EPA	United State-Environmental Protection Agency
UV-VIS	Ultra Violet Visible
VCC	Viable Cell Count
WHO	World Health Organization

Dedicated to Maa-Deuta Mainu-Maini-Ton