

CONTENTS

ABSTRACT	i
LIST OF TABLES	ii
LIST OF FIGURES	iii
1. Introduction	1
1.1 Global energy scenario	1
1.2 Indian energy scenario	3
1.3 Energy and industrial scenario in North East India	4
1.4 Technology prospect of renewable energy in North East India	4
1.5 Biomass gasification	5
1.5.1 Gasification process and reactor types	6
1.5.2 Feedstock characteristics and gasifier performance	9
1.5.3 Assessment of gasifiers performance	10
1.5.4 Prediction of performance of gasifiers through modelling	11
1.6 Justification for present study and objectives	12
2. Review of Literature	14
2.1 Biomass gasification for heat and power generation in India	14
2.2 Thermodynamic equilibrium models for prediction of producer gas composition and performance of gasifiers	15
3. Methods and materials	20
3.1. Use of stoichiometric equilibrium model for determination of composition of producer gas	20
3.2. Determination equilibrium constants	23
3.3. Model inputs	25
3.3.1. Elemental composition of feedstock	25
3.3.2. Moisture content of feedstock	26
3.3.3. Moles of air supplied for specific values of equivalence ratio	26
3.3.4. Temperature of gasification zone	26

3.4. Model outputs	27
3.4.1. Composition of producer gas	27
3.4.2. Lower heating value of the producer gas	27
3.4.3. Overall conversion efficiency	28
3.5. Experimental Procedure	29
3.5.1. Feedstock characterization	29
3.5.2. Experimental set up	29
3.5.3. Test procedure	29
4. Results and Discussion	34
4.1 Feedstock characterization	34
4.2 Model inputs	35
4.2.1 Elemental composition of the feedstock	35
4.2.2. Moisture content of feedstock	36
4.2.3. Assessment of moles of air supplied for specific values of equivalence ratio	36
4.3 Simulation results of stoichiometric equilibrium model	37
4.3.1 Composition of producer gas	37
4.3.2 Lower heating value of the producer gas	42
4.3.3. Overall conversion efficiency	44
4.4. Experimental results	46
5. Conclusions	48
References	49

LIST OF TABLES

Table 1.1	World's total energy consumption by fuel, for year 2006-2035 (Quadrillion Btu)	3
Table 1.2	Typical gasification reactions at 25 °C	7
Table 3.1	Gibbs free energy, heat of formation at 298 K, 1 atm and empirical coefficients for gases used in the model	24
Table 3.2	Equilibrium constants used in the model	25
Table 3.3	Test procedure for the analysis	25
Table 3.4	Lower heating value of constituents of producer gas at 25 °C	28
Table 3.5	Dimensions of gasifier system, Ankur make, closed top downdraft throated	30
Table 4.1	Local and scientific name of wood species of the study	34
Table 4.2	Proximate analysis and lower heating value of feedstocks	35
Table 4.3	Ultimate analysis of feedstocks	35
Table 4.4	Chemical representation of the feedstocks	36
Table 4.5	Moles of steam (d) for considered moisture contents	36
Table 4.6	Moles of air supplied for specific values of equivalence ratio	37
Table 4.7	Conversion efficiency for bamboo assessed through experiments	47
Table 4.8	Conversion efficiency for wood mixture assessed through experiments	47

LIST OF FIGURES

Fig. 1.1	Potential path for gasification	6
Fig. 3.1	Inputs and outputs of stoichiometric equilibrium model	23
Fig. 3.2	Schematic of test gasifier system	31
Fig. 3.3	Gasification System at laboratory	31
Fig. 3.4	Junker's calorimeter	32
Fig. 3.5	Digital anemometer	32
Fig. 4.1	Producer gas composition vs. equivalence ratio for Bamboo at 800 °C, 10% MC, wb	38
Fig. 4.2	Producer gas composition vs. equivalence ratio for Wood mixture at 800 °C, 10% MC, wb	38
Fig. 4.3	Gas composition vs. gasification temperature for Bamboo at ER 0.25, 10% MC, wb	39
Fig. 4.4	Gas composition vs. gasification temperature for wood mixture at ER 0.25, 10% MC, wb	40
Fig. 4.5	Gas composition vs. Moisture content for bamboo at 800 °C and ER 0.25	41
Fig. 4.6	Gas composition vs. Moisture content for wood mixture at 800 °C and ER 0.25	41
Fig. 4.7	LHV of producer gas vs. ER at different temperatures for bamboo at 10% MC	43
Fig. 4.8	LHV vs. moisture content for bamboo at 800 °C and ER 0.25	44
Fig. 4.9	Conversion efficiency vs. ER at different temperature for bamboo, 10% MC, (wb)	45
Fig. 4.10	Conversion efficiency vs. ER at different Temperature for wood mixture, 10% (wb)	46