

Table of Contents

<i>Acknowledgement</i>	i
<i>Abstract</i>	iii
<i>Table of Contents</i>	iv
<i>List of Figures</i>	vi
<i>List of Tables</i>	viii
<i>Nomenclature</i>	ix
Chapter 1: Introduction	1
1.1 Motivation	1
1.2 Fluidized bed technology	2
1.3 Fluidized bed drying	4
1.4 Objectives of the present work	6
1.5 Outline of the thesis	6
Chapter 2: Literature Review	8
2.1 Introduction	8
2.2 Bed hydrodynamics and mass transfer behaviour	8
2.3 Effect of operating parameters on fluidized bed drying	10
2.4 Drying mechanism	12
2.5 Summary of the literature review	14
Chapter 3: Methodology	15
3.1 Introduction	15
3.2 Description of the Fluidized Bed Dryer Setup	15
3.3 Description of the Ergun's Simulation Software	18
3.4 Design of Air heater	20
3.4.1 Air heater Design	20
3.4.2 Heating Coil calculation	21

3.5	Experimental procedure	23
3.6	Summary of the chapter	23
Chapter 4: Results and Discussion		25
4.1	Ergun's Fluidization Software Results	25
4.1.1	Solid Characteristics	25
4.1.2	Grid Design	26
4.1.3	Flow Structure	27
4.1.4	Cyclone Design	27
4.1.5	Pressure Drop Calculation	28
4.1.6	Heat transfer Co-efficient Calculation	29
4.2	Experimental results	29
4.3	Validation of results	39
Chapter 5: Conclusions and scope for future work		40
Reference		41
Appendices		45
I	Calculation of minimum fluidization velocity	45
II	Design of distributor plate	46
III	Design of cyclone separator	51
IV	Calibration of Blower for air supply	54
V	List of Equipment/Instruments used	55

List of Figures

Fig. 1.1	Various forms of contacting of a batch of solids by fluid	3
Fig. 2.1	Geldart classification of particles for air at ambient conditions	9
Fig. 2.2	Types of moisture	13
Fig. 2.3	Batch drying curve, constant drying condition	13
Fig. 3.1	Schematic of the fluidized bed paddy dryer Experimental setup	16
Fig. 3.2	Photograph of the fluidized bed paddy dryer Experimental setup	17
Fig. 3.3	Pitot tube connected with manometer	18
Fig. 3.4	Photographs of the designed cyclone separator	18
Fig. 3.5	Straight hole type distributor plate	18
Fig. 3.6	Photograph of glass wool insulation	18
Fig. 3.7	Schematic representation of different section of the FB	19
Fig. 3.8	Schematic Air heater design	21
Fig. 3.9	Photographs of the designed electric air heater	22
Fig. 3.10	Photographs of the blower used connected with variac for speed regulation	22
Fig. 4.1.1	Solid Characteristics of the Fluidized Bed	25
Fig. 4.1.2	Grace Diagram	26
Fig. 4.1.3	Pressure drop profile of the Grid	26
Fig. 4.1.4	Flow Structure within the BFB	27
Fig. 4.1.5	Cyclone Design curve	28
Fig. 4.1.6	Pressure Drop at different section of the FB	28
Fig. 4.1.7	Variation of HTC with Solid Volume fraction	29
Fig. 4.2.1	Drying rate curve for I= 600g, U=10.2 m/s, T=75°C, P=2 KW	30
Fig. 4.2.2	Drying rate curve for I= 600g, U=10.75 m/s, T=60°C, P=2 KW	31
Fig. 4.2.3	Drying rate curve for I= 600g, U=10.67 m/s, T=60°C, P=1.5 KW	32
Fig. 4.2.4	Drying rate curve for I= 500g, U=10.67 m/s, T=60°C, P=1.5 KW	33
Fig. 4.2.5	Drying rate curve for I= 500g, U=14 m/s, T=60°C, P=2 KW	34
Fig. 4.2.6	Drying rate curve for I= 500g, U=9.5 m/s, T=75°C, P=2 KW	35
Fig. 4.2.7	Drying rate curve for I= 400g, U=9.5 m/s, T=60°C, P=2 KW	36
Fig. 4.2.8	Drying rate curve for I=600g at different operating conditions	37
Fig. 4.2.9	Drying rate curve for I=500g at different operating conditions	37

Fig. 4.2.10 Drying rate curves for the experiments performed at different operating conditions 38

List of Tables

Table 4.1.1	HTC Obtained from the different models	29
Table 4.2.1	Moisture removed against time for I= 600g, U=10.2 m/s, T=75°C, P=2 KW	30
Table 4.2.2	Moisture removed against time for I= 600g, U=10.75 m/s, T=60°C, P=2 KW	31
Table 4.2.3	Moisture removed against time for I= 600g, U=10.67 m/s, T=60°C, P=1.5 KW	32
Table 4.2.4	Moisture removed against time for I= 500g, U=10.67 m/s, T=60°C, P=1.5 KW	33
Table 4.2.5	Moisture removed against time for I= 500g, U=14 m/s, T=60°C, P=2 KW	34
Table 4.2.6	Moisture removed against time for I= 500g, U=9.5 m/s, T=75°C, P=2 KW	35
Table 4.2.7	Moisture removed against time for I= 400g, U=9.5 m/s, T=60°C, P=2 KW	36
Table 4.3.1	Comparison of the experimental results with other researchers results	39

Nomenclature

A_b	: Cross-sectional area of the bed (m^2)
C_d	: Orifice discharge co-efficient
d_{or}	: Orifice diameter (m)
d_p	: Particle diameter (m)
ε	: Voidage
ε_{mf}	: Voidage at minimum fluidization
H_{mf}	: Height of the bed at minimum fluidization (m)
h	: Heat transfer co-efficient (W/m^2-K)
Δh	: Difference in height of manometric fluid of water column (cm)
I	: Bed inventory (Kg)
N_{or}	: Number of orifices in the distributor
ΔP_b	: Bed pressure drop (N/m^2)
ΔP_d	: Distributor pressure drop (N/m^2)
t	: Time required for drying (min)
T	: Temperature ($^{\circ}C$)
U_{mf}	: Minimum fluidization velocity (m/s)
U_t	: Terminal Velocity (m/s)
V	: Supply Voltage (volts)
ρ_g	: Gas Density (Kg/m^3)