

CONTENTS

| Content | Page no. |
|-----------------------------------------------------------|------------|
| List of Figures | i |
| List of Tables | iii |
| List of abbreviation | v |
| Chapter 1: Introduction | 1 |
| 1.1 Solar PV panel | 1 |
| 1.2 Battery | 2 |
| 1.3 Battery charge/ discharge controller | 2 |
| 1.4 Inverter | 3 |
| 1.5 Low voltage protection circuit | 6 |
| 1.6 Light dimmers | 6 |
| 1.6.1 Mainstream dimmers. | 6 |
| 1.6.1.1 Phase cut dimmers (leading & trailing edge) | 6 |
| 1.6.1.2 Mainstream dimmers: Compatible load(R/C/L dimmer) | 7 |
| 1.7 Light emitting diodes | 8 |
| 1.8 <i>Compact fluorescent lamp</i> | 9 |
| 1.8.1 Construction | 9 |
| 1.9 Functioning of a liquid repellent | 10 |
| 2.0 Objective of the present work | |
| Chapter 2: Literature reviews | 11 |
| 2.1 Introduction | 11 |
| 2.2 Literature review | 11 |
| 3.3 Summary of literature review | 16 |
| Chapter 3: Methodology | 17 |
| 3.1 Methodology | 17 |
| 3.1.1 Selection of stages | 17 |
| 3.1.1.1 Solar charge controller | 18 |
| 3.1.1.2 Low voltage indicator circuit | 22 |

| | |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------|
| 3.1.1.3 Inverter selection | 25 |
| Chapter 4: Experimental Model Development | 28 |
| 4.1 Charge controller development | 28 |
| 4.2 Low voltage indicator circuit development | 29 |
| 4.3 Inverter circuit development | 31 |
| Chapter 5: Results and Discussion | 34 |
| 5.1 Simulation results of conventional inverter | 34 |
| 5.2 Inverter performance testing | 35 |
| 5.3 Average energy delivered in a short period of time | 39 |
| 5.4 Average energy conserved in a short period of time | 40 |
| 5.5 Comparison of light intensity with power delivered for CFL and LED based lantern without mosquito repellent operation | 42 |
| 5.6 Solar lantern performance testing with height and distance adjustment by using open holder design for LED based solar lantern | 44 |
| 5.7 Comparison in the effectiveness of closed casing and open holder design of solar lantern | 46 |
| 5.8 Battery backup calculation | 47 |
| Conclusions | 50 |
| Future work | 51 |
| References | 52 |
| Appendix-I | 54 |

List of Figures

- Fig.1.1 Equivalent circuit of the solar cell
- Fig.1.2 A single-phase bridge inverter with gating signals and output voltage
- Fig.1.3 MOSFET characteristics Curves
- Fig.1.4 Leading edge dimmer
- Fig.1.5 Trailing edge dimmer
- Fig.1.6 Type of loads
- Fig.1.7 Light dimmer circuit
- Fig.1.8 Light emitting diode structure description
- Fig.1.9 Liquid mosquito repellent
- Fig.2.1 Battery low voltage indicator circuit
- Fig.3.1 Methodology used for designing the solar lantern
- Fig.3.2 Solar charge controller schematic
- Fig.3.3 555 timer integrated circuit
- Fig.3.4 Low voltage indicator circuit diagram
- Fig.3.5 Voltage divider circuit diagram
- Fig.3.6 Schematic of square wave inverter by using 4047 IC
- Fig.4.1 Perforated Printed circuit board design of solar charge controller
- Fig.4.2 Perforated Printed circuit board design of Low voltage indicator circuit
- Fig.4.3 Perforated printed circuit board design of Inverter
- Fig.4.4 All the circuits fabricated PCBs container with dimmer switch
- Fig.4.5 Picture of all the components used in development of solar lantern
- Fig.4.6 Complete developed kit with all the fixtures and accessories
- Fig.4.7 Height adjustment flexibility demonstration in open holder design of the solar lantern
- Fig.5.1 Simulated circuit of a conventional full bridge inverter using MOSFET
- Fig.5.2 Voltage and current output waveforms of the above full bridge inverter
- Fig.5.3 Comparison of efficiency at different dimmer switch positions without LMR operation
- Fig.5.4 Comparison of efficiency at different dimmer switch positions at normal mode of LMR
- Fig.5.5 Comparison of efficiency at different dimmer switch positions at active mode of LMR

- Fig.5.6 Comparison in average energy delivered in 5 min to the load in three different dimmer switch positions during all the operations
- Fig.5.7 Comparison in average energy conserved in 5 min in three different dimmer switch positions during all the operations
- Fig.5.8 Comparison of Light Intensity with dimmer switch position for CFL and LED based lantern without mosquito Repellent
- Fig.5.9 Light intensity measurement in open holder design in two different adjustments of height
- Fig.5.10 Battery backup with different loads at three different dimmer switch positions
- Fig.5.11 Instruments used during experiments

List of Tables

| | |
|------------|--------------------------------------------------------------------------------------------------------------------------------|
| Table 2.1 | Illumination produced by a 9W solar powered lantern at different distances |
| Table 2.2 | Price and the life of different units of a solar powered lantern scheme. |
| Table 2.3 | Comparison of light between LEDs and a 60-w bulb |
| Table 3.1 | Terminal connection and output period |
| Table 4.1 | Components used in designing of solar charge controller |
| Table 4.2 | Components used in designing of Low voltage indicator circuit |
| Table 4.3 | Components used in designing of Inverter |
| Table 5.1 | Inverter Performance Testing |
| Table 5.2 | Average energy delivered in a short period of time |
| Table 5.3 | Average energy conserved in a short period of time |
| Table 5.4 | Comparison of illumination with power delivered for CFL and LED based lantern without mosquito Repellent |
| Table 5.5 | Solar lantern performance testing with height and distance adjustment by using open holder design for LED solar lantern design |
| Table 5.6 | Comparison of effectiveness of closed casing design and open holder design |
| Table 5.7 | Backup calculation in LED Bulb without LMR operation |
| Table 5.8 | Backup calculation in LED Bulb with NLMR operation and dimmer switch positions |
| Table 5.9 | Backup calculation in CFL without LMR operation and dimmer switch positions |
| Table 5.10 | Backup calculation in CFL with NLMR operation and dimmer switch positions |

List of Abbreviation

| | |
|---------------------------------|---------------------------------------------------------------------------|
| LMR | Liquid mosquito repellent |
| CFL | Compact fluorescent lamp |
| LED | Light emitting diode |
| NLMR | Liquid mosquito repellent in normal mode |
| ALMR | Liquid mosquito repellent in active mode |
| f | Output frequency in Hz |
| V_d or V_b | voltage at which power delivered in volts or Battery voltage |
| I_d or I_b | Current from battery to load or delivered current to load in amp |
| P_d or P_b | Power delivered to the load or from the battery in watt |
| V_o | Output voltage from the inverter in volt |
| I_o | Output current from the inverter output to the Load in mili amp |
| P_o or P_c | Output power or power consumed by the load |
| E_d | Energy delivered from the battery to the load |
| $E_{d1}, E_{d2}, \dots, E_{d5}$ | Energy delivered from the battery in respective dimmer switch positions |
| E_c | Energy conserved by using light dimmers switch |
| E_{c1} | Energy conserved from dimmer switch 3 to dimmer switch 1= $E_{d3}-E_{d1}$ |
| E_{c2} | Energy conserved from dimmer switch 5 to dimmer switch 1= $E_{d5}-E_{d1}$ |
| E_{c3} | Energy conserved from dimmer switch 5 to dimmer switch 3= $E_{d5}-E_{d3}$ |
| a_1, a_2, a_3, a_4 | Diagonal distances from lantern on a table during experiments |
| b, c | Straight distances from lantern placed on experiment table |
| h_1 | Minimum height of the open holder stand |
| h_2 | Maximum height of the open holder stand |