

## TABLE OF CONTENTS

	<b>Page no.</b>
LIST OF FIGURES	i-ii
LIST OF TABLES	iii-iv
LIST OF ABBRIVIATION	v
<b>Chapter 1: INTRODUCTION</b>	<b>1</b>
1.1 Renewable energy in India	3
1.2 Biomass	6
1.2.1 Biomass utilization in India	7
1.3 Pyrolysis	8
1.4 Bio-oil	10
1.4.1 Physicochemical properties of bio-oil	10
1.4.2 Bio-oil from biomass	10
1.4.3 Components of bio-oil	11
1.5 Biochar	12
1.6 World wide tea production	13
1.6.1 Tea production in India	14
1.6.2 Main tea producing region in India	15
1.6.3 Source of tea factory waste	15
1.7 Energy from waste	16
1.7.1 Generation of solid waste in India	17
1.8 Justification of the work	19
1.9 Objective of the work	21
1.10 Organization of thesis	22
<b>Chapter 2: LITERATURE RIVEW</b>	<b>23</b>
2.1 Waste to energy conversion	23
2.2 Pyrolysis	24

2.3	Pyrolysis heating rate	25
2.4	Vapour rescedence time	27
2.5	Literature reviews related to bio-oil	28
2.6	Chemical nature of bio-oil	28
2.7	Upgrading of bio-oil	29
2.8	Lignocellulosic composition	31
2.9	Biochar	32
2.10	p <sup>H</sup> of biochar	34
2.11	Porosity and surface area	35
2.12	Thermogravimetric analysis of biomass	36

### **Chapter 3: MATERIALS AND METHODS** 38

3.1	Material used	38
3.2	Methodology	40
3.2.1	Pretreatment (drying)	40
3.2.2	Pyrolysis at different temperature	40
3.3	Proximate analysis of samples	40
3.3.1	Determination of moisture content	40
3.3.2	Determination of ash content	41
3.3.3	Determination of volatile matter	41
3.3.4	Determination of fixed carbon content	42
3.4	Component analysis of the biomass samples	42
3.4.1	Analysis of extractives	42
3.4.2	Analysis of hemicellose	42
3.4.3	Analysis of lignin	43

3.4.4	Analysis of cellulose	43
3.5	Ultimate analysis	43
3.6	Determination of p <sup>H</sup>	44
3.7	Calorific value	44
3.8	Experimental setup for pyrolysis	44
3.9	Product yield	46
3.10	Carbon sequestration potential (CS)	46
3.11	Conductivity of biochar	46
3.12	Cation exchange capacity	47
3.13	Characterization of bio-oil	47
3.13.1	Calorific value	47
3.13.2	Total acid number	47
3.14	Instrumental Characterization	48

## **Chapter 4: RESULTS AND DISCUSSION** 49

4.1	Characterization of the selected biomass sample	49
4.1.1	Proximate analysis	49
4.1.2	Ultimate analysis	49
4.1.3	Bio-chemical and inorganic element analysis	52
4.2	FTIR TFW samples	52
4.3	SEM-EDX analysis	54
4.4	TGA analysis	55
4.5	Pyrolysis product yields of TFW	58
4.6	Characterization of biochar	61
4.6.1	Elemental analysis of biochar	62

4.6.2	p <sup>H</sup> of biochar	62
4.6.3	FTIR spectroscopy of biochar	63
4.6.4	SEM image of biochar at different temperature	63
4.6.5	EDX-analysis of biochar at 500°C	67
4.7	Carbon sequestration potential (cs)	68
4.8.	Cation exchange capacity (CEC) of TFW biochar	68
4.8	Conductivity of TFW biochar	69
4.9	Characterization of bio-oil yielded from TFW	69
4.9.1	Ultimate analysis	69
4.9.2	FTIR spectra of bio-oil	70
4.10	<sup>1</sup> H NMR of bio-oil	73
4.11	GC-MS of bio-oil	78
<b>Chapter 5: CONCLUSION</b>		<b>79</b>
5.1	Pictorial presentations -Appendix	80
5.2	References	82
5.3	publications	83

## LIST OF FIGURES

		<b>Page no.</b>
Fig 1	2012 fuel shares in world Total Primary Energy Supply	2
Fig 2	Potential and current installed capacity of renewable sources of energy in India.	4
Fig 3	Renewable Energy Potential in India	6
Fig 4	Available biomass sources	7
Fig 5	Simplified representation of biomass pyrolysis	8
Fig 6	Tea producing countries of the world	13
Fig 7	Waste management hierarchy	18
Fig 8	Green tea leaves	36
Fig 9	Tea Factory Waste samples	36
Fig 10	Flow diagram of methodology adopted for study	37
Fig 11	Schematic figure of the experimental setup	43
Fig 12	Experimental set up available in the lab	43
Fig 13	Vertical reactor tube of glass	43
Fig 14	FTIR of Tea Factory Waste	51
Fig 15	SEM analysis of FTW	52
Fig 16	EDX analysis of FTW	53
Fig 17	TGA of TFW	55
Fig 18	TGA and DTG of TFW	55
Fig 19	Yield of pyrolysis products of TFW at different temperature with 10°C/min heating rate	57
Fig 20	Yield of pyrolysis products of TFW at different temperature with 40°C/min heating rate	58
Fig 21	Effect of temperature on P <sup>H</sup> of biochar produced from TFW at different heating rates	61
Fig 22	FTIR Spectra of TFW biochar obtained at Different temperature	62
Fig 23	Biochar at 400°C	63
Fig 24	Biochar at 500°C	64
Fig 25	Biochar at 600°C	64
Fig 26	Biochar at 700°C	65

Fig 27	EDX graph of biochar at 500°C	65
Fig 28	FTIR of TFW bio-oil at 400°C, 500°C respectively	69
Fig 29	FTIR of TFW bio-oil at 600°C, 700°C respectively	70
Fig 30	<sup>1</sup> H-NMR of FTW Bio-oil yielded at 400°C	72
Fig 31	<sup>1</sup> H-NMR of FTW Bio-oil yielded at 500°C	73
Fig 32	<sup>1</sup> H-NMR of FTW Bio-oil yielded at 600°C	74
Fig 33	<sup>1</sup> H-NMR of FTW Bio-oil yielded at 700°C	75
Fig 34	GC-MS of TFW bio-oil	76
Fig 35	TIC of TFW bio-oil	77

## LIST OF TABLES

		<b>Page no.</b>
Table1.1	Total renewable energy installed capacity	5
Table1.2	Typical product yields (dry wood basis) obtained by different modes of thermochemical conversion of wood	9
Table1.3	Components of crude biomass oil	11
Table1.4	The top ten tea producing countries in the world, with the number of tons of tea produced in 2013	12
Table1.5	Chemical composition of Tea Factory Waste and Decaffeinated Tea Wastes ( <i>Camellia assamica</i> )	15
Table 4.1	Proximate analysis and heating value of selected samples	48
Table 4.2	Component analysis of TFW (%wt dry basis)	50
Table 4.3	Metal content in the TFW (wavelength/nm)	50
Table 4.4	Functional groups present in TFW	51
Table 4.5	EDX of TFW	53
Table 4.6	Effect of temperature and heating rate on the pyrolysis product yield of TFW	56
Table 4.7	Proximate analysis of biochar produced from TFW at different temperatures and heating rates	59
Table 4.8	Elemental analysis of biochar produced at different temperature and heating rate	60
Table 4.9	P <sup>H</sup> of biochar at different temperature with different heating rate.	60
Table 4.10	EDX analysis of biochar at 500°C	65
Table 4.11	Carbon sequestration potential of biochar	66
Table 4.12	CEC of TFW biochar	66
Table 4.13	Conductivity of TFW biochar	67
Table 4.14	Ultimate analysis of bio-oil obtained at 500°C	67
Table 4.15	<sup>1</sup> H NMR results of bio-oils of TFW	71
Table 4.16	Results of chemical compounds of TFW bio-oil obtained at 500°C	78

## **LIST OF ABBRIVIATION**

<b>ATS</b>	Automatic Transfer Switch
<b>CEC</b>	Cation Exchange Capacity
<b>CS</b>	Carbon Sequestration
<b>DCTW</b>	Decaffeinated Tea Waste
<b>GHG</b>	Green House Gases
<b>HHR</b>	High Heating Rate
<b>HVF</b>	Hot Vapour Filtration
<b>MSW</b>	Municipal Solid Waste
<b>PGM</b>	Plasma Gasification Melting
<b>SHR</b>	Slow Heating Rate
<b>TFW</b>	Tea Factory Waste
<b>WTE</b>	Waste To Energy