

CONTENTS

	Page No.
LIST OF FIGURES	iii
LIST OF TABLES	v
LIST OF ABBREVIATIONS	vi
LIST OF NOMENCLATURE	vi
CHAPTER 1: INTRODUCTION	1
1.1 Thermal performance	2
1.2 Building envelope	4
1.2.1 Orientation of the building	5
1.2.2 Building constituents	5
1.2.3 Window glazing	5
1.2.4 Thermo-physical properties of building envelope	6
1.2.5 Time lag and decrement factor	6
1.2.6 Role of thermal mass	7
1.3 Thermal insulation	7
1.3.1 Thermal insulation materials	8
1.3.2 How thermal insulation works	9
1.3.3 Benefits of thermal insulation	10
1.4 TRNSYS simulation tool	10
CHAPTER 2: LITERATURE REVIEW	13
CHAPTER 3: OBJECTIVES AND METHODOLOGY	20
3.1 Objectives	20
3.2 Methodology	21
3.2.1 TRNSYS model generation	23
3.2.2 Thermal transmittance or U value calculation	26
3.2.3 Time lag and decrement factor calculation	27
3.2.4 Window to wall ratio	28
3.2.5 Procedure for plotting the graphs	28
CHAPTER 4: RESULTS AND DISCUSSION	29
4.1 Variation of overall heat transfer coefficient	29
4.2 Comparison of different insulation materials	33

4.3 Different positions of insulation materials	35
4.4 Window glazing	36
4.5 Analysis for different orientation	38
4.6 Increasing window to wall ratio	40
4.7 Roof with and without insulation	41
4.8 Windows with overhang and without overhang	42
4.9 Comparison of inside and outside wall temperatures	44
4.10 Time lag and decrement factor for different wall thickness	45
4.11 Time lag and decrement factor for different positions of insulation materials	46
4.12 Optimized building model analysis	47
CHAPTER 5: CONCLUSIONS	50
REFERENCES	52
PUBLICATION	57

LIST OF FIGURES

Figure	Particulars	Page No.
1.1	Thermal simulation flow paths of a building	3
1.2	Heat transfer processes occurring in a wall	4
1.3	Schematic representation of time lag and decrement factor	7
1.4	Thermal comparison of common building materials	9
1.5	Utilization share of TRNSYS among other simulation programs	11
3.1	Methodology for the study	21
3.2	2-D layout of the house with single zone	22
3.3	Systematic approach for building simulation	23
3.4	Configurations considered for different locations of insulation material	25
3.5	Building layout for different orientations considered for the simulation	26
4.1	Daily minimum zone temperature for different wall thickness	29
4.2	Daily maximum zone temperature for different wall thickness	30
4.3	Minimum zone temperature for wall with same thickness	31
4.4	Maximum zone temperature for wall with same thickness	31
4.5	Minimum zone temperature for wall with maximum thickness	32
4.6	Maximum zone temperature for wall with maximum thickness	33
4.7	Surface temperature of three different insulation materials for January	34
4.8	Surface temperature of three different insulation materials for July	34
4.9	Inner surface temperature for January for three different positions of insulation	35
4.10	Inner surface temperature for July for three different positions of insulation	36
4.11	Daily minimum zone temperature in January for glazed windows	36
4.12	Daily maximum zone temperature in July for glazed windows	37
4.13	Minimum and maximum zone temperatures for different orientations	38
4.14	Daily minimum zone temperature in January for different window to wall ratio	40
4.15	Daily maximum zone temperature in January for different window to wall ratio	41
4.16	Daily minimum zone temperature in January for roof with insulation and without insulation	41

4.17 Daily maximum zone temperature in July for roof with insulation and without insulation	42
4.18 Daily minimum zone temperature for windows with and without overhang	42
4.19 Daily maximum zone temperature for windows with and without overhang	43
4.20 Inside and outside wall surface temperatures for different thicknesses (January)	44
4.21 Inside and outside wall surface temperatures for different thicknesses (July)	45
4.22 Time lag and decrement factor for different wall thickness (January)	45
4.23 Time lag and decrement factor for different wall thickness (July)	46
4.24 Time lag and decrement factor for various position of insulation	47
4.25 Comparison of optimized temperature profile to the original temperature profile for the month of January and July	48

LIST OF TABLES

Table	Particulars	Page No.
3.1	Physical properties of the selected vernacular house of base case	21
3.2	Thermo physical Properties of the Materials Used for construction of <i>Building Envelope</i>	22
3.3	Wall Configuration Considered For the Simulation	24
3.4	Configuration considered for roof and floor	24
4.1	<i>Parameters of the building model considered and the</i> optimized building model	47

LIST OF ABBREVIATIONS

HVAC	Heating, Ventilation and Air-conditioning
ASHRAE	American Society of Heating, Refrigerating, and Air conditioning
AAC	Autoclaved Aerated Concrete
XPS	Extruded Polystyrene
EPS	Expanded Polystyrene
ACH	Air Change Per Hour
PPD	Predicted Percentage of Dissatisfied
PMV	Predicted Mean Vote
TRNSYS	Transient Simulation Tool
WWR	Window to Wall Ratio

LIST OF NOMENCLATURE

U-value	Overall heat transfer coefficient
\emptyset	Time lag
f	Decrement factor
R_T	Thermal resistance
K	Thermal conductivity
T_o^{\max}	Inside maximum temperature
T_o^{\min}	Inside minimum temperature
T_e^{\max}	Outside maximum temperature
T_e^{\min}	Outside minimum temperature
A_o	Amplitude of inside wave
A_e	Amplitude of outside wave