

Contents

Contents	vii
List of Figures	ix
1 Introduction	1
1.1 Wireless Sensor Network	1
1.2 Motivation	2
1.3 Problem Definition	2
1.4 Organization of the report	2
2 Literature survey and background knowledge	3
2.1 S-MAC	3
2.2 T-MAC	3
2.3 Q-MAC	3
2.4 Energy-Efficient Wake-Up Scheduling for Data Collection and Ag- gregation	4
2.5 Energy-Balanced Transmission Policy	4
2.6 Pairwise	4
3 Proposed Architecture	5
3.1 Time slot allocation	5
3.2 Initialization phase	7
3.3 Grid size calculation	7
3.4 Latency reduction	10
3.5 Packets Transfer Scenario of RTS and CTS	10
4 Proposed Protocol	12

5 Results and Discussions	15
6 Conclusion and Future Works	20
Bibliography	21

List of Figures

1.1	Wireless Sensor Network	1
3.1	Example of a grid based quorum	6
3.2	Example of intersections. Host A and Host B meet each other at intervals 2 and 6	6
3.3	Network divided into adjacent coronas centered at the sink node. The i th corona is denoted as C_i	7
3.4	Table1:Ratio of traffic loads for networks with different coronas .	8
3.5	Table2:Relationship between the traffic inter-arrival time and the grid size of Corona 1 in four corona network.	9
3.6	Example showing next hop group	10
4.1	State transition diagram of sender side	13
4.2	State transition diagram of receiver side	14
5.1	Table 3 :Specifications of simulation scenario	15
5.2	The Simulation Scenario where node n_0 is acting as base node. . .	16
5.3	Plot of throughput of different nodes and the overall throughput.	16
5.4	Table 4:Energy Settings	17
5.5	Plot of remaining Energy in nodes 5, 7 and 12	17
5.6	Table 5:Control Packets vs. Data Packets	18
5.7	End to End delay for single hop in nodes 5, 7 and 12	18
5.8	Table 6:Average Delay for packet transfer	19