

# Contents

Contents	vii
List of Figures	ix
<b>1 Introduction</b>	<b>1</b>
1.1 Motivation . . . . .	2
1.2 Objective . . . . .	3
1.3 Dissertation Organization . . . . .	4
<b>2 Localization</b>	<b>5</b>
2.1 Introduction . . . . .	5
2.2 Components of Localization Systems . . . . .	5
2.3 Classification of Localization Protocols . . . . .	6
2.3.1 Range-based Methods . . . . .	7
2.3.1.1 Received Signal Strength Indicator (RSSI) . . . . .	7
2.3.1.2 Time Difference of Arrival(TDoA) . . . . .	7
2.3.1.3 Time of Arrival (AoA) . . . . .	8
2.3.2 Position Estimation . . . . .	8
2.3.2.1 Trilateration and Multilateration . . . . .	9
2.3.2.2 Triangulation . . . . .	9
2.3.3 Range-free Methods . . . . .	10
2.3.3.1 Ad-hoc Positing System(APS) . . . . .	10
2.3.3.2 Point-in-Triangulation Test . . . . .	11
2.4 Flip ambiguities in WSN localization . . . . .	12
2.5 Discussion . . . . .	13

<b>3 Related Works</b>	<b>14</b>
3.1 Introduction . . . . .	14
3.2 Path Planning . . . . .	14
3.3 Path Planning for a Mobile Anchor . . . . .	16
3.3.1 SCAN . . . . .	16
3.3.2 DOUBLE SCAN . . . . .	16
3.3.3 HILBERT . . . . .	17
3.4 Path Planning for a Group of Mobile Anchor . . . . .	18
3.5 Discussion . . . . .	18
<b>4 Proposed Work</b>	<b>19</b>
4.1 System Model and Assumption . . . . .	19
4.1.1 Optimal beacon point selection . . . . .	19
4.2 Proposed Mobile anchor Trajectory . . . . .	20
4.2.1 Random Deployment . . . . .	20
4.2.2 Grid Deployment . . . . .	20
4.3 Proposed algorithm . . . . .	21
4.3.1 Path length . . . . .	22
4.4 Performance Evaluation . . . . .	22
4.4.1 Simulation Settings . . . . .	22
4.4.2 Simulation Results . . . . .	23
4.4.2.1 Localization errors . . . . .	24
4.5 Challenges exist when implementing localization in WSN . . . . .	24
<b>5 Conclusion and Future Work</b>	<b>26</b>
5.1 Conclusion . . . . .	26
5.2 Future Work . . . . .	26
<b>Bibliography</b>	<b>29</b>

# List of Figures

2.1	Components of localisation Systems . . . . .	6
2.2	classification of localization protocols . . . . .	6
2.3	Range base methods . . . . .	9
2.4	Localization using trilateration . . . . .	10
2.5	Trangulation . . . . .	10
2.6	DV-hop correction example . . . . .	11
2.7	Area based APIT algorithm overview . . . . .	12
2.8	Flip ambiguity . . . . .	13
3.1	One mobile anchor moving in S-shaped trajectory . . . . .	15
3.2	a)SCAN,b)DOUBLE SCAN,c)HILBERT . . . . .	17
3.3	Group of Mobile Anchor Nodes Network Model . . . . .	18
4.1	Beacon point selection . . . . .	20
4.2	Sensor nodes are randomly deployed and a mobile anchor moving in equilateral triangle trajectory . . . . .	21
4.3	Grid based deployment of nodes and a mobile anchor moving in equilateral triangle trajectory . . . . .	21
4.4	Trilateration based localization . . . . .	24
4.5	Grid based deployment and a mobile anchor(blue coloured) node moves around the region and localized all nodes(red coloured) . .	24
4.6	localization vs number of nodes . . . . .	25
.1	Trilateration . . . . .	27